



ETL LISTED  
COMPLIES WITH UL1838

PROJECT	DATE
TYPE	CATALOG #

## FLAT SIDE PATH AP-390B

### KEY FEATURES

- CONTEMPORARY DESIGN
- SOLID BRASS
- REFLECTIVE WHITE COATING FOR MAXIMUM LIGHT OUTPUT
- UV PROTECTED FROSTED ACRYLIC LENS
- HIGH TEMPERATURE SOCKET
- FIELD REPLACEABLE LED

### PRODUCT SPECIFICATION

LENS	FROSTED ACRYLIC
SOCKET	BI PIN
LAMP	ENCAPSULATED T3/G4
VOLTAGE	9-18V AC/DC
LIGHT SPREAD	6-8 FT AVG
LEAD WIRE	3 FT

### STEP 1

#### FIXTURE CONFIGURATION

**AP-390B**

FINISH OPTION

- NBZ NATURAL BRONZE
- SS STAINLESS STEEL

### STEP 3

#### ACCESSORY OPTIONS

**AX-800P  
INCLUDED**

STAKE OPTION

- AX-800P STANDARD SLOTTED STAKE
- AX-802P HEAVY DUTY PERMA POST

### STEP 2

#### LED LAMP CONFIGURATION

**LED-T3**

LED WATTAGE

- 1.5W 110 LM
- 2.5W 210 LM
- 3.5W 280 LM

KELVIN TEMPERATURE

- 27K 2700K
- 30K 3000K

ENCAPSULATED

ENC ENCAPSULATED (IP67)

+ Dimmable: See [ENCAPSULATED T3 LED Lamps Spec Sheet](#) for additional details (1.5w, 2.5w, 3.5w only)