

E-Mail: sales@coronalighting.com

FAX.

(800) 727-9957

(800) 727-9262 (213) 747-4500

(213) 747-3234



ARCHITECTURAL GRADE SERIES

## **SPECIFICATION SHEET**

Cast Brass

## **Fixture Specifications:**

Housing & Shroud: Corrosion Resistant Cast Brass.

PRODUCT #: CL-518B-AB

Finish: AB- Antique Bronze. Natural toning process.

AB finish will vary due to artistic process.

Lens: Frosted and heat resistant tempered flat glass,

supplied with extra clear lens, linear glass lens,

and honeycomb louver.

Socket: Top grade fixed ceramic bi-pin socket.

12V, MR-16, 50W max. Lamp:

Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Wiring: Fixture is prewired with a 5ft 18-2 SPT2-W direct

burial cord. Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting.

Directional Lights

Gasket: Silicone gasket for water tight sealing

Knuckle: Adjustable cast brass knuckle with thumb screw

and 1/2" NPT threaded male hub on bottom.

Mounting Spike: Standard injection molded spike with ½" NPT

threaded female hub.

Electrical Notes: A remote 12V transformer is required. Options are

available from Corona Lighting.


Voltage range for LED lamps are 9V-17V. Proper grease/lubricant is suggested on threaded parts during installation process.

Warranty: Limited lifetime warranty on fixture housing against

manufacturer's defects.







LAMP NUMBER	WATTS	BEAM SPREAD	LUMEN	_ COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt
Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET						

**JOB INFORMATION** 

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

TOTAL QUANTITY:

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - lamp - wattage - lamp angle CL - 518B-AB - L-ED16 - 5W -

Example: CL-518B-AB-L-ED16-5W-FL FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.





(800) 727-9957 (800) 727-9262 (213) 747-3234

E-Mail: sales@coronalighting.com

(213) 747-4500



ARCHITECTURAL GRADE SERIES

## **ACCESSORIES SHEET**

 Cast Brass Directional Lights

### **Mounting Pedestals**

CX-601-BK 1" PVC Mounting Pedestal, 1/2" NPT, Black

PRODUCT #: CL-518B-AB


CX-601-VG 1" PVC Mounting Pedestal, ½" NPT, Verde Green

CX-603-BK 3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub

on top, Black

3" PVC Mounting Pedestal, 1/2" NPT Female Brass Hub CX-603-VG

on top, Verde Green



CX-604-BK 1" PVC Adjustable Mounting Pedestal, 1/2" NPT, Black

CX-621-BK 1" PVC Cap, 1/2" NPT, Black

1" PVC Cap, 1/2" NPT, Verde Green CX-621-VG

CX-622-BK 2" PVC Cap, 1/2" NPT, Black

CX-622-VG 2" PVC Cap, 1/2" NPT, Verde Green

3" PVC Cap, 1/2" NPT Female Brass Hub, Black CX-624-BK

CX-624-VG 3" PVC Cap, 1/2" NPT Female Brass Hub, Verde Green

# **Ground Spikes**

CX-642-BK 8.5" ABS Spike, 1/2" NPT, Black

CX-642-BZ 8.5" ABS Spike, 1/2" NPT, Bronze

CX-643-BZ 8.5" ABS Spike, 1/2" NPT, Bronze



CX-647-BK

CX-646-BK 8" ABS Spike, 1/2" NPT, Black

8" ABS Spike, 1/2" NPT, Natural Brass CX-646-BR

CX-646-SS 8" ABS Spike, 1/2" NPT, Stainless Steel

CX-647-BK 10.5" Heavy Duty ABS Spike, 1/2" NPT, Black

### **Mounting Canopies**

CX-705B-AB Brass Flat Canopy, 1/2 NPT, Antique Bronze CX-709B-AB Brass Raised Canopy, 1/2 NPT, Antique Bronze CX-718B-AB 5" Brass Canopy, 3-Hole ½ NPT, Antique Bronze

CX-719B-AB Brass Tree Mounting Bracket, 1/2" NPT, Antique Bronze

CX-720-BR Brass Tree mount Canopy with 9" Rubber Strap

stretches to 14, Natural Brass

CX-721-BR Brass Tree mount Canopy with 15" Rubber Strap

stretches to 22", Natural Brass

CX-722-BR Brass Tree mount Canopy with 22" Rubber Strap

stretches to 33", Natural Brass

CX-723-BR Brass Tree mount Canopy with 31" Rubber Strap

stretches to 45", Natural Brass


CX-724-BR Brass Tree mount Canopy with 41" Rubber Strap

stretches to 61", Natural Brass

## **Mounting Risers**

CX-682B-AB 6" Brass Riser, ½ NPT Male/Female, Antique Bronze CX-683B-AB 12" Brass Riser, 1/2 NPT Male/Female, Antique Bronze CX-684B-AB 18" Brass Riser, ½ NPT Male/Female, Antique Bronze CX-685B-AB 24" Brass Riser, ½ NPT Male/Female, Antique Bronze





(800) 727-9957

FAX. (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com



ARCHITECTURAL GRADE SERIES

# **ACCESSORIES SHEET**

Directional Lights

Cast Brass

### **Mounting Posts For Sign Light & Path Light Applications**

CX-678B-AB 24" Brass Single Head Post, Antique Bronze CX-679B-AB 24" Brass Double Head Post, Antique Bronze CX-690B-AB 18" Brass Single Head Post, Antique Bronze CX-693B-AB 18" Brass Double Head Post, Antique Bronze

PRODUCT #: CL-518B-AB

•CX-718B-AB (Mounting Canopies pg 2) is required for sign light installation.



#### **Cable Connectors**

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

CX-858 Speedy Cable Connector, Supply Cable up to 10-2, Black

CX-839 Universal cable connector, Supply cable up to 8-2,

one/Pack Black



#### Special Lenses & Honeycomb Louvers

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
<b>C</b> X-242	MR-16 lens, Frosted
CX-243	MR-16 lens, Prismatic

For MR-16 Lenses and Louvers, you will need the CX-238

