

SPECIFICATION SHEET

TEL.FAX.(800) 727-9262(800) 727-9957(213) 747-4500(213) 747-3234

1633 Staunton Ave Los Angeles, CA 90021

E-Mail: sales@coronalighting.com

1

	UCT # : C	L-0305	3-AB		•Area	Lights	• Cast Brass
Fixture	Specificatio	ons:					
Housing:	- Corrosion resistant	cast brass.			Wiring	J:	Fixture is prewired with a 3-ft 18-2 direct burial col
Stem:	Solid brass pipe with	folid brass pipe with $\frac{1}{2}$ " NPT on bottom.					 Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are available from Corona Lighting. Standard injection molded spike with ½" NPT threaded female hub. A remote 12V transformer is required. Options are
Finish:			Natural toning process.		Mount	ing Spike	
Lens:	Frosted polycarbonate, cover over lamp providing sprinkler water protection. Top grade fixed ceramic bi-pin socket. Easy tool free lamp access.			ng			
Socket:				bl			available from Corona Lighting. Voltage range for LED lamps are 8V-21V. Proper grease/lubricant is suggested on
Lamp:	12V, T3, 20W max. Available in LED (2\ See Lamp guide be				Warra	nty:	threaded parts during installation process. Limited lifetime warranty on fixture housing and stem against manufacturer's defects.
				2W a	E D and 2.5		$ \begin{array}{c} 21"\\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ $
VAILABLI	E LED LAMPS (Coro			imited warran	ty against man	ufacturer's defect	$ \begin{array}{c} \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ $
AMP NUMBE	_	ona LED lamps ha BE/ SPREAD				ufacturer's defects HALOGEN EQUIVALEN	s) JOB INFORMATION
AMP NUMBE -EDT3-2W	R WATTS	BE	AM C LUMEN 200	imited warran COLOR & TEMP. 2700K	ty against man RATED HOURS 25,000	ufacturer's defects HALOGEN EQUIVALEN 20 Watt	s) JOB INFORMATION
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3	WATTS 2 V 2.5 3K 2	BE/ SPREAD 360° 180° 360°	AM C LUMEN 200 240 210	imited warran COLOR & TEMP. 2700K 2700K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000	ufacturer's defect: HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt	$\begin{array}{c c} & & & \\ & & & \\ & & & \\ \hline \\ & & & \\ \hline & & \\ \hline & & & \\ \hline \\ \hline$
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W	WATTS 2 2 2.5 3K 2 V-3K 2.5	BE/ SPREAD 360° 180°	AM C LUMEN 200 240 210	imited warran COLOR & TEMP. 2700K 2700K	ty against manu RATED HOURS 25,000 25,000	ufacturer's defects HALOGEN EQUIVALEN 20 Watt 35 Watt	$\begin{array}{c c} & & & \\ & & & \\ & & & \\ \hline \\ & & & \\ \hline & & \\ \hline & & & \\ \hline \\ \hline$
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W -EDT3-AM*	WATTS 2 V 2.5 3K 2 V-3K 2.5 2 2	BE/ SPREAD 360° 180° 360° 180°	AM C LUMEN C 200 240 210 250	imited warran COLOR & TEMP. 2700K 2700K 3000K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defect. HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS:
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W -EDT3-AM* AM- Amber colo	WATTS 2 V 2.5 3K 2 V-3K 2.5 2 2	BE/ SPREAD 360° 180° 360° 180° 360°	AM C LUMEN 200 240 210 250 170	imited warran COLOR & TEMP. 2700K 2700K 3000K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defect. HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #:
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W -EDT3-AM*	WATTS 2 2.5 3K 2 V-3K 2.5 2 2	BE/ SPREAD 360° 180° 360° 180° 360°	AM C LUMEN 200 240 210 250 170	imited warran COLOR & TEMP. 2700K 2700K 3000K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defect. HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY:
-EDT3-2W -EDT3-2.5W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W -EDT3-AM*	WATTS 2 2.5 3K 2 V-3K 2.5 2 2	BE/ SPREAD 360° 180° 360° 180° 360°	AM C LUMEN 200 240 210 250 170	imited warran COLOR & TEMP. 2700K 2700K 3000K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defect. HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	s) JOB INFORMATION TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE:
AMP NUMBE -EDT3-2W -EDT3-2.5W -EDT3-2W-3 -EDT3-2.5W -EDT3-AM*	WATTS 2 2.5 3K 2 V-3K 2.5 2 2	BE/ SPREAD 360° 180° 360° 180° 360°	AM C LUMEN 200 240 210 250 170	imited warran COLOR & TEMP. 2700K 2700K 3000K 3000K	ty against manu RATED HOURS 25,000 25,000 25,000 25,000	ufacturer's defect. HALOGEN EQUIVALEN 20 Watt 35 Watt 20 Watt 35 Watt	s) JOB INFORMATION T TYPE: DATE: JOB NAME & ADDRESS: PRODUCT #: TOTAL QUANTITY: LAMP TYPE & WATTAGE: TRANSFORMER:

• CL - product # - lamp - wattage

Example: CL-650B-AB-L-EDT3-2W-3K

CL - 650B-AB - L-EDT3 - 2W-3K
 Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.





Cable Connectors

2⁷/₈"

CX-705B-AB

2³/₄"

CX-709B-AB

CX-718B-AB