

TEL.

(800) 727-9262

(800) 727-9957

(213) 747-4500

(213) 747-3234



SPECIFICATION SHEET

E-Mail: sales@coronalighting.com

#### PRODUCT #: CL-807-D-SI

•Flexible BBQ- Deck Light

• Steel & Aluminum

#### **Fixture Specifications:**

ARCHITECTURAL GRADE SERIES

Head: Diecast aluminum head, chrome plated

Arm: Flexible steel arm, available in 24" and 36" lengths.

Finish: Chrome plated fixture, in SI- Silver Plated finish.

Also available in BK-Black.

Lens: Clear, tempered and heat resistant glass.

12V, MR-16, 35W max.

Socket: Top grade bi pin socket Lamp:

> Available in LED (3.5W & 5W) or without lamp. See the Lamp Guide below for more information.

Mounting: 3" round cast aluminum base canopy, chrome plated

with on/off push button covered by rubber boot.

Wiring: Fixture is prewired with a 3ft direct burial cable.

Wire connector sold seperately. Universal connector (CX-839) and silicone filled wire nut (CX-854) are

available from Corona Lighting.

**Electrical Notes:** A remote 12V transformer is required. Options are

available from Corona Lighting.

Voltage range for LED lamps are 9V-17V.


Some assembly needed. Proper grease/lubricant is suggested on threaded parts during installation.

Warranty: Limited lifetime warranty on fixture housing against

manufacturer's defects.







AVAILABLE LED LAMPS	(Corona LED lamps have a <b>five (5)</b> year limited warranty against manufacturer's defects)
---------------------	--

LAMP NUMBER	WATTS	BEAM SPREAD	// LUMEN	_ COLOR & TEMP.	RATED HOURS	HALOGEN EQUIVALENT
L-ED16-3W-SP	3.5	15° Spot	270	2700K	50,000	25 Watt
L-ED16-3W-FL	3.5	45° Flood	270	2700K	50,000	25 Watt
L-ED16-3W-WF	3.5	60° Wide Flood	270	2700K	50,000	25 Watt
L-ED16-5W-SP	5	15° Spot	350	2700K	50,000	40 Watt
L-ED16-5W-FL	5	45° Flood	350	2700K	50,000	40 Watt
L-ED16-5W-WF	5	60° Wide Flood	350	2700K	50,000	40 Watt
L-ED16-COB5W-SP	5	15° Spot	450	2700K	50,000	50 Watt
L-ED16-COB5W-FL	5	38° Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-WF	5	60° Wide Flood	450	2700K	50,000	50 Watt
L-ED16-COB5W-SP3K	5	15° Spot	470	3000K	50,000	50 Watt
L-ED16-COB5W-FL3K	5	38° Flood	470	3000K	50,000	50 Watt
L-ED16-COB5W-WF3K	5	60° Wide Flood	470	3000K	50,000	50 Watt

TYPE: DATE:

JOB NAME & ADDRESS:

PRODUCT #:

**TOTAL QUANTITY:** 

LAMP TYPE & WATTAGE:

TRANSFORMER:

CONTRACTOR:

SPECIFIER:

• When ordering LED lamp with a fixture your part number should follow the format below:

• CL - product # - Length lamp - wattage - lamp angle CL - 807-D-SI -- L-ED16 -5W

■ Single color MR-16 LED available in AMBER, BLUE, GREEN, PURPLE, RED and VIOLET

36

Example: CL-807-D-SI-36-L-ED16-5W-FL

Corona Lighting reserves the right to make any change and/or improvement to the design and construction of this fixure without further notification.



ARCHITECTURAL GRADE SERIES

## **ACCESSORIES SHEET**

CX-243

1633 Staunton Ave Los Angeles, CA 90021

FAX. (800) 727-9957 (800) 727-9262 (213) 747-3234 (213) 747-4500

E-Mail: sales@coronalighting.com

• Steel & Aluminum

### PRODUCT #: CL-807-D-SI

#### **Cable Connectors**

CX-854 Direct Burial Silicone Filled Wire Nut, Tan

CX-858 Speedy Cable Connector, Supply Cable up to 10-2, Black

CX-839 Universal cable connector, Supply cable up to 8-2,

one/Pack Black







# Special Lenses & Honeycomb Louvers

•Flexible BBQ- Deck Light

CX-238	MR-16 Snap-on holder, Silver Plated
CX-239	MR-16 honeycomb louver, Black
CX-240-AM	MR-16 color lens, Amber
CX-240-BL	MR-16 color lens, Blue
CX-240-GR	MR-16 color lens, Green
CX-240-RD	MR-16 color lens, Red
CX-240-YL	MR-16 color lens, Yellow
CX-241	MR-16 lens, Linear Spread
CX-242	MR-16 lens, Frosted

• For MR-16 Lenses and Louvers, you will need the CX-238

MR-16 lens, Prismatic

