




PROJECT	DATE
TYPE	CATALOG #



ETL LISTED
COMPLIES WITH UL1838

BIG SMOKY

FL-105B

KEY FEATURES

- FULLY ADJUSTABLE SHROUD FOR GLARE CONTROL
- CAST BRASS
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- DIMMABLE*
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP

PRODUCT SPECIFICATIONS

MATERIAL	CAST BRASS
LENS	CLEAR CONVEX
SOCKET	BI PIN
LAMP	MR16
VOLTAGE	9-15V AC/DC
PROJECTION	UP TO 50 FT
LEAD WIRE	3 FT

STEP 1

FIXTURE CONFIGURATION

FL-105B

FINISH

NBZ NATURAL BRONZE

STEP 3

ACCESSORY OPTIONS

AX-800P

INCLUDED

STAKE OPTION

AX-800P STANDARD SLOTTED STAKE

AX-802P HEAVY DUTY PERMA POST

SURFACE/TREE MOUNT OPTION

AX-803B DEEP ROUND BASE (NBZ)

AX-804B ROUND BASE (NBZ)

+ See accessory spec sheet for additional mounting options

STEP 2

LED LAMP CONFIGURATION

LED-MR16

LED WATTAGE

3.5W 280 LM

4.5W 320 LM

5.5W 420 LM

6.5W 470 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

41K 4100K*

55K 5500K*

BEAM ANGLE

15D 15° NARROW **

45D 45° STANDARD

60D 60° WIDE

* Dimmable: See MR16 LED Lamps Spec Sheet for additional details
 * Available in 45° only
 ** Available in 3.5w & 5.5w, 3000K only