



ETL LISTED
COMPLIES WITH UL1838

PROJECT	DATE
TYPE	CATALOG #

NEPTUNE H20-502B

KEY FEATURES

- HEAVY CAST BRASS
- ADJUSTABLE FOR PRECISE LIGHT PROJECTION
- 25 FT UNDERWATER RATED SJ CABLE WIRE
- 50 FT & 100 FT SJ CABLE WIRE OPTIONS
- HIGH TEMPERATURE SOCKET
- FIELD REPLACEABLE LED

PRODUCT SPECIFICATION

MATERIAL	CAST BRASS
FINISH	NATURAL BRASS
LENS	CLEAR FLAT TEMPERED
SOCKET	BI PIN
LAMP	MR16
MAX LAMP	35W
VOLTAGE	12V AC/DC
PROJECTION	UP TO 35 FT
MAX DEPTH	UP TO 6 FT

STEP 1

FIXTURE CONFIGURATION

H20-502B

LEAD OPTION

50 50 FT LEAD

100 100 FT LEAD

*Standard Lead is 25 FT

Leave blank if you want standard option

STEP 2

LED LAMP CONFIGURATION

LED-MR16

LED WATTAGE

3.5W 250 LM

4.5W 350 LM

5.5W 430 LM

KELVIN TEMPERATURE

27K 2700K

30K 3000K

41K 4100K

55K 5500K

BEAM ANGLE

15D 15° NARROW *

45D 45° STANDARD

60D 60° WIDE**

INSTALLATION NOTE: It is important to hand tighten and seal this fixture with silicone before placing the fixture into water. For added protection - Apply silicone around the outside of the front cap and the bottom cord exit.

* 15° Only available in 3.5w & 5.5w - 3000k

** 60° Available in 3.5w, 4.5w, 5.5w, 2700k or 3000k

+ Consult factory for additional options