


LH7 - 6" NON IC HOUSING 6" LINE VOLTAGE HOUSINGS



Standard: 75W PAR30/R30, 150W PAR38, 50W PAR16/PAR20, 100W A19

SPECIFICATION

120V 150W Max R30/PAR30/PAR38/
A19 MED E26

Application: General purpose recessed downlight housing for medium to high ceilings for residential and light commercial applications. A variety of trims, compatible styles and finishes are available to achieve the proper décor and illumination.

Housing: Pre-wired housing adjusts up to a 1 1/2" ceiling thickness. Integral thermal protector to guard against improper lamping and installation. Housing provides an adjustable socket plate which allows for use of different lamp types. Trim is secured with torsion wing springs/standard coil springs or serrated clips.

Mounting: Housing suitable for new construction installations only, supplied with (2) 24" adjustable hanger bars with 90 degrees repositioning ability. Hanger bars equipped with nail-less install 3/4" serrated barbed studs and with captive nails, for faster and easier secure mounting in wood joists. Set-screws lock into position and prevent shifting after installation. Earthquake structural cable compatible for drop panel ceiling or any other mounting that requires direct support from structural ceilings.

Socket: Standard porcelain medium screw base socket with high temperature leads.

Junction Box : 16 gauge pre-wired galvanized steel Junction Box, 32 cubic-inch for a maximum of (8) #12 AWG wires. Furnished with (7) 3/4" and (4) Romex knock-outs. Strain clamps to install or remove covers for easy access and ground wire. Equipped with safety standard fitting for flex-conduit.

Insulation Contact: Non-IC rated housing must be kept 3" from insulation.

Airflow: Airtight option is designed to restrict air flow from room into plenums in compliance to the WSEC - Washington State Energy Code, (Less than 2.0 CFM -Cubic Feet per Minute). Complies to Title24 air flow requirements (Air-tight).

Safety Labels: UL/CUL listed for through-branch wiring (8) No.12 AWG 90°C and suitable for damp locations. NYC approved: Calendar #41937.

Label: UL Listed



COMPATIBILITY

 LFB2012 FIRE BARRIER	 LRELD603 6" GU24 LED BAFFLE (1100LM)	 LRP30 PHENOLIC PAR30 BAFFLE
 LRS101 BAFFLE W/ CLEAR REFLECTOR	 LRS12 ALBALITE LENS W/ REFLECTOR	 LCMPD7R ROUND 7" LUMEN PAD - 1200LM
 LR330 GIMBAL RING	 LR38 REGRESSED EYEBALL W/ BAFFLE	 LRS105 WALL WASH W/ REFLECTOR BAFFLE
 LRS95 WALL WASH W/ REFLECTOR	 LR16 SHOWER TRIM W/ OPAL LENS	 LR48 ADJUSTABLE EYEBALL W/ BAFFLE
 LCMLD56 6" SURFACE MOUNT LUMEN DISC	 LR12 SHOWER TRIM W/ ALBALITE LENS	 LR380 DECO GLASS RING-SHAPED

Please see website for more compatible items.

FEATURE:



ORDERING EXAMPLE : LH7

LH7	RATING
LH7	Blank :Standard
A	:Airtight

ID#: 1