

# JOSH LED PUCK

Adjustable or Fixed  
12V or 24V / 300lm

Slim LED disk light for accent, under cabinet, in- cabinet, niche, and jewelry cases, and other applications with limited space. These low-profile fixtures can be spaced together to provide excellent and even illumination on all surfaces. Josh luminaires do not produce diode image and can be recessed or surface mounted. Combined with ultra low-profile housing, Nora's light disk offers unique features and a great ease of installation. LED technology eliminates forward heat from the fixture, also no UV or infrared rays to harm artwork, retail displays or heat sensitive foods. Josh LED Puck produces more light than a traditional 20W xenon or halogen puck while consuming only 3.5W.

## FEATURES

- 12V or 24V input
- 300 lumens / 3.5W
- Well suited for very small spaces
- Recessed or Surface Mounted
- Easy installation
- Dimmable with dimmable power supply
- 12" to 48" extension cables accessory available
- 2700K, 3000K, 3500K or 4000K @ 90+CRI
- No flicker delay or warm up like compact fluorescent products
- No diode image
- No UV light or infrared wavelengths
- cULus Listed for Damp Location
- 5-Year Limited Warranty



### JOSH LED PUCK

TYPE	CCT	FINISH
<b>NMP-A</b> 12V Adjustable	<b>27</b> 2700K	<b>B</b> Black
<b>NMP-LED</b> 12V Fixed	<b>30</b> 3000K	<b>BZ</b> Bronze
<b>NMP2-A</b> 24V Adjustable	<b>35</b> 3500K	<b>BN</b> Brushed Nickel
<b>NMP2-LED</b> 24V Fixed	<b>40</b> 4000K	<b>W</b> White

Example: **NMP-A30BZ** - 12V Josh Adjustable, 3000K, Bronze finish



# JOSH LED PUCK LIGHT ACCESSORIES



Recessed Flange for Adjustable

<a href="#">NMP-ARECB</a>	Black
<a href="#">NMP-ARECBN</a>	Brushed Nickel
<a href="#">NMP-ARECBZ</a>	Bronze
<a href="#">NMP-ARECW</a>	White

Used to install NMP-A or NMP2-A in a recessed application.  
Note: Not needed for fixed puck.



6-Port Power Line Interconnect

<a href="#">NMPK-6P-24B</a>	Black
<a href="#">NMPK-6P-24W</a>	White

Terminal block connects up to six LED Josh Puck lights to a Nora driver. Includes 24" cord with RCA jack.



Extension Cable

<a href="#">NMPA-EW-12</a>	12" Cable
<a href="#">NMPA-EW-24</a>	24" Cable
<a href="#">NMPA-EW-36</a>	36" Cable
<a href="#">NMPA-EW-48</a>	48" Cable

Finish: Black (B), White (W)

Used to extend the length of the cable from the puck to the terminal block. Linkable up to 10'.



In-Line Touch Dimmer

[NATL-518W](#)

72W max., no power fail memory, touch on/off and hold to dim.



Direct Plug-In LED Driver

<a href="#">NAPK-524W/12</a>	12V 24W
<a href="#">NAPK-560W/12</a>	12V 60W
<a href="#">NATL-524W</a>	24V 24W
<a href="#">NATL-545W</a>	24V 45W
<a href="#">NATL-596W</a>	24V 96W

Voltage: 120V

Dimming: Non-Dimmable



Class II Hardwire LED Driver with Regulator, MLV dimming

<a href="#">NAPK-5030HW/12</a>	12V 30W
<a href="#">NAPK-5060HW/12</a>	12V 60W
<a href="#">NATL-5030HW</a>	24V 30W
<a href="#">NATL-5100HW</a>	24V 100W

Voltage: 120-240V

Dimming: Non-Dimmable

Requires: 10' Power Line Connector



Class II Hardwire LED Driver with Regulator, MLV dimming

<a href="#">NMTD-40/12D</a>	12V 40W
<a href="#">NMTD-60/12D</a>	12V 60W
<a href="#">NMTD-60/24D</a>	24V 60W
<a href="#">NMTD-96/24D</a>	24V 96W

Voltage: 120-277V

Dimming: Magnetic Low Voltage

Regulator: Integral regulator for constant current and voltage

Includes: 10' Power Line Connector



Class II Hardwire LED Driver ELV dimming

<a href="#">NAPKED-5040HW</a>	12V 35W
<a href="#">NAPKED-5060HW</a>	12V 60W
<a href="#">NATLED-5040HW</a>	24V 40W
<a href="#">NATLED-5075HW</a>	24V 75W

Input Voltage: 120V

Dimming: Electronic Low Voltage

Includes: 10' Power Line Connector



Class II Hardwire LED Driver 0-10V dimming

<a href="#">NATL-5060-12-HWD10</a>	12V 60W
<a href="#">NATL-5096-24-HWD10</a>	24V 96W

Voltage: 120-277V

Dimming: 0-10V

Includes: 10' Power Line Connector



Class II Hardwire LED Driver with Breakers, MLV dimming

<a href="#">NMT-244/12C2D1</a>	120/12V 240W
<a href="#">NMT-244/12C2D1</a>	277/12V 240W
<a href="#">NMT-303/24C2D1</a>	120/24V 300W
<a href="#">NMT-303/24C2D1</a>	277/24V 300W

Input Voltage: 120V or 277V

Dimming: Magnetic Low Voltage

Requires: 10' Power Line Connectors



Power Line Connector

<a href="#">NATL-10</a>	10' Cable
<a href="#">NATL-30</a>	30' Cable

For use with Class II drivers. Carries output from driver, requires power line cable.

5" Power Line Splitter

<a href="#">NATL-302W</a>	5" Cable
---------------------------	----------



Low Voltage Splice Box

[NATL-415W](#)

Use to join low voltage lead to low voltage power line connector or interconnector.



16AWG In-Wall Rated Wire

<a href="#">NATL-W16-2-250</a>	16AWG 250'
<a href="#">NATL-W16-2-20</a>	16AWG 20'

16 AWG low voltage Class II two-conductor, in-wall rated wire.



2' Wire Raceway

<a href="#">NATL-422B</a>	Black
<a href="#">NATL-422W</a>	White

Field-cutable plastic. Includes wire channel with double faced tape and cover.