



RHL4R-ICAT

4" IC Air-tight Remodel LED Housing

PROJECT: _____



MODEL #: _____

LOCATION: _____

CONTACT: _____



DIMENSIONS



USE OF PRODUCT

The RHL4R-ICAT is the ideal product for general purpose recessed LED housing for residential, commercial, hospitality, health care, restaurant and retail applications.

CONSTRUCTION

- Minimum Clearance "IC" or insulated ceiling housings are rated for direct contact with insulation. No minimum clearance is required.
- CEILING THICKNESS Up to 1 1/4.
- BAR HANGERS Bar Hangers are adjustable from 13-5/8" to 25" and can be repositioned to 90° on plaster frame. Pre-installed "real nail" easily installs in wood or composite joists.
- JUNCTION BOX Junction box is listed for through branch circuit wiring and contains seven 7/8 knockouts and four ROMEX pryouts with Romex cable clamp. Ground wire provided on J-Box.
- REMODEL FRAME Galvanized steel construction
- CONNECTION Quick connect provided for easy connection to REC Series LED module to meet non-screw base socket requirements per California Title 24.

LABELS/COMPLIANCE

cUL listed
Certified under ASTM-283 for Air-Tight Construction
Title 24 Compliant

4" IC Air-Tight Remodel LED Housing

ORDERING INFO

RHL4R-ICAT

Series

RHL4R-ICAT - 4" IC Air-Tight Remodel LED Housing



www.rayonlighting.com
info@rayonlighting.com

tel: 323.446.2626
fax: 323.446.2606

Specification and product availability
subject to change without notice

04/18