



RSL4 (0-10V Luminaire)

4" SURFACE LUMINAIRE WITH GLARE CONTROL

JOB INFORMATION

Type: _____
Catalog No: _____
Project Name: _____
Comments: _____
Prepared by: _____

RSL4

FEATURES

USE OF PRODUCT

Great solution for residential, multifamily, and hospitality interior applications where a surface mount fixture is desired. This fixture offers glare control lens, five color temperature selectability, and may be paired with a fire-rated j-box to meet 2-hour requirements.

RSL4 (0-10V LUMINAIRE) FEATURES

- Wattage Selectable: 8W, 10W, 12W
- Color Temperature Selectable: 2700K, 3000K, 3500K, 4000K, 5000K
- CRI: 90+
- Voltage/Dimming: 120-277V (0-10V)
- Visual Comfort: Glare control lens

COLOR TEMPERATURE SELECTABLE

Color temperature selectable luminaire allows for easy control between 2700K, 3000K, 3500K, 4000K, and 5000K.

LENS

Specially designed lens designed for visual comfort and optimum glare control.

LUMINAIRE CONSTRUCTION

Luminaire is constructed of aluminum heat sink for maximum LED heat dissipation and polycarbonate body which is great for dead-front applications.

OPTIONAL FIRE-RATED ENCLOSURE

Constructed of 16-gauge galvanized steel to meet 2-hour fire requirements. Comes standard with adjustable bar hangers (14"-24") for wood joist ceiling installations. Luminaire enclosure may be adjusted vertically to accommodate varying ceiling thicknesses.

INSTALLATION

Fixture may be mounted to a 3" or 4" octagonal junction box (supplied by others) or with the RFJ-S-R42 (Fire Rated Enclosure) by Rayon Lighting.

LISTINGS/COMPLIANCE/WARRANTY

- ETL listed
- Energy Star certified
- State of California Title 24 and JA8 compliant
- Wet location rated
- UL 263 (2-hour fire-rated)
- IC rated
- Air-tight ASTM-E283
- 5-year limited warranty

WATT AND LUMEN CHART

WATTS	LUMENS	CRI
8W	550 lm	90+
10W	750 lm	90+
12W	950 lm	90+



LUMINAIRE ORDERING INFO

SERIES	WATTS	COLOR TEMPERATURE	VOLTAGE	FINISH
RSL4	WS12 - Wattage Selectable (8W, 10W, 12W)	5CTS - Color Temperature Selectable (2700K, 3000K, 3500K, 4000K, 5000K)	UNV - 120-277V	W - White

OPTIONAL FIRE-RATED ENCLOSURE ORDERING INFO


SERIES

RFJ-S-R42 - Fire-Rated Enclosure

RSL4 (0-10V Luminaire)

4" SURFACE LUMINAIRE WITH GLARE CONTROL

SURFACE MOUNT DIMENSIONS



RFJ DIMENSIONS

