



PROJECT	DATE
TYPE	CATALOG #

UP/DOWN LIGHT W-701B



KEY FEATURES

- SURFACE MOUNT - UP AND DOWN LIGHT
- SOLID BRASS
- NATURAL BRONZE FINISH GUARANTEED NOT TO CHIP, FLAKE OR PEEL
- DIMMABLE*
- TEMPERED, SHOCK AND HEAT RESISTENT LENS
- HIGH TEMPERATURE CERAMIC SOCKET
- FIELD REPLACEABLE LED LAMP

PRODUCT SPECIFICATIONS

MATERIAL	SOLID BRASS
LENS	CLEAR FLAT TEMPERED
SOCKET	BI-PIN
LAMP	MR16
VOLTAGE	9-18V AC/DC
PROJECTION	UP TO 35 FT
BACK PLATE	3" DIAMETER
LEAD WIRE	3 FT

STEP 1 FIXTURE CONFIGURATION

W-701B	NBZ
FINISH	
NBZ NATURAL BRONZE	

STEP 2 LED LAMP CONFIGURATION

LED-MR16			
LED WATTAGE			
3.5W	280 LM		
4.5W	320 LM		
5.5W	420 LM		
KELVIN TEMPERATURE			
27K	2700K		
30K	3000K		
41K	4100K*		
55K	5500K*		
BEAM ANGLE			
15D	15° NARROW**		
45D	45° STANDARD		
60D	60° WIDE		

Note: Requires 2 LED lamps for up/down functionality

* Dimmable: See [MR16 LED Lamps Spec Sheet](#) for additional details
 * Available in 45° only
 ** Available in 3.5w & 5.5w, 3000K only

BACK PLATE INFO: Evenly cast light up and down.
 Can be also be used as only an up light or down light by only using one LED lamp