

SPECIFICATION SHEET



SPECIFICATIONS

INPUT VOLTAGE	12V AC/DC	
POWER CONSUMPTION	2.0W	
LUMEN OUTPUT	65 Lumens	
OUTPUT CURRENT	35mA	
сст	3000K / 4000K	
CRI	85+	
DIMMING	NO	
MOUNTING	Surface mount	
OPERATING TEMPERATURE	-4 ~ 122°F (-20 ~ 50°C)	
AMBIENT TEMPERATURE	-4 ~ 176°F (-20 ~ 80°C)	
LUMEN MAINTENANCE	50,000 hrs.	
CONNECTION	7" 18AWG Lead Wire	
WARRANTY	3-Year Limited	
HOUSING DIMENSIONS	2.75"W x 1.75"H x 1"D	
FACE PLATE DIMENSIONS	4.75"W x 3"H x 3/8"D	














JOB NAME: LOCATION: QUOTE/REF#:


The **ST-300** is a 2W indoor/outdoor non-dimming LED steplight designed to provide safe illumination for paths and walkways with a stylish look. This versatile step light features a wide variety of trim plates and finishes to choose from. It is constructed of high impact, weather-resistant ploycarbonate material and can last up to 50,000 hours, maintenance-free. The **ST-300** can be mounted either vertically or horizontally.

FEATURES

- Easy install with single gang switch box.
- Suitable for indoor/outdoor applications.
- Louvered, Lensed and Visor face plate options.
- Bronze, Brushed Nickel and White color finishes.
- Die-cast aluminum face plates.
- 3000K and 4000K color temperature options.
- NON-dimmable

DIMENSIONS





ORDERING GUIDE EX: ST300-30K-HL-BZ-12V

ST300					
MODEL	COLOR TEMP	FACE PLATE OPTIONS		FINISH	VOLTAGE
	30K - 3000K 40K - 4000K AM - Amber BL - Blue	HL - Horizontal Louver HV - Horizontal Visor HW - Horizontal Wave HDL - Horizontal Designer Louver LS - Lensed	VL - Vertical Louver VV - Vertical Visor VW - Vertical Wave VDL - Vertical Designer Louver	WH - White BZ - Bronze BN - Brushed Nickel	UNV - 120/277V 12V - 12V AC/DC



FACE PI	LATE O	PTIONS
---------	--------	--------

LS - Lensed



HL - Horizontal Louver



HV - Horizontal Visor



HW - Horizontal Wave



HDL - Horizontal Designer Louver





FACE PLATE OPTIONS

VL - Vertical Louver



W - Vertical Visor



vw - Vertical Wave



VDL - Vertical Designer Louver

