



MODULE

**DRD4**

Adjustable Downlight

DRD4M

SUMMARY

ADJUSTMENT: 360° directional aim, 45° tilt**SLOPE CEILING COMPATIBILITY:** up to 45° tilt**LED CHIP:** Cree**DELIVERED MODULE LUMENS:** 750 lm (9.7W), 1000 lm (12.0W)**EFFICACY:** 82 lm/W**COLOR QUALITY:** 93+ CRI, 2-step SDCM**CCT:** 2700K, 3000K, 3500K, 4000K**BEAM SPREAD:** Narrow Spot (15°), Spot (25°), Flood (40°), Linear Spread (60° x 30°), Soft Focus**CONNECTOR:** PowerPlug® Luminaire Disconnect Model 182**INPUT VOLTAGE:** 120/277V, 50/60Hz**DIMMING:** Down to less than 1% for TRIAC/ELV at 120V, 0-10V or Lutron EcoSystem at 120/277V**MAX INPUT CURRENT (120V):** 0.130 amps**MAX INPUT CURRENT (277V):** 0.065 amps**POWER FACTOR:** Greater than 0.9**TOTAL HARMONIC DISTORTION:** Less than 20%**AMBIENT OPERATING TEMPERATURE:** -20°C to 40°C**PHOTOMETRIC TESTING:** Tested in accordance to IESNA LM-79-2008**LISTINGS:** ENERGY STAR® qualified*, California Title 24 2016 JA8 compliant, UL Listed for Damp Location, UL Certified US-CA, Declare**LIFETIME:** 50,000 hours at 70% lumen maintenance**WARRANTY:** 5 year limited warranty

WARM DIM OPTION

LED: Bridgelux LED, **DELIVERED MODULE LUMENS):** 1000 lm (12.0W),**EFFICACY:** 83 lm/W, **CCT RANGE:** 3000K - 1800K, **MAX INPUT CURRENT (120V):** 0.11 amps, **MAX INPUT CURRENT (277V):** 0.047 amps

* Refer to ENERGY STAR Certified light fixtures database

PRODUCT BUILDER - TRIAC/ELV & 0-10V

M SERIES HOUSING

PRODUCT CODE		INSTALLATION		SHAPE		RATING	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
M4	4" Housing	NC	New Construction	R	Round	S	Standard
		CP	Chicago Plenum ¹			F	Fire Rated
		LT	Low Profile, TRIAC/ELV (3" Plenum) ²				
		LO	Low Profile, 0-10V (3" Plenum) ²				
		DH	Double Housing ^{1,3}				
		RM	Remodel				

M4CC	Concrete Tight ²
-------------	-----------------------------

DRD MODULE

PRODUCT CODE		LUMENS		CRI		CCT		BEAM SPREAD		FINISH		DIMMING	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
DRD2M	Fixed	07	750 lm	9	93+ CRI	27	2700K	GA	General Ambient (90°+) ⁴	[Blank]	Black	T	TRIAC/ELV
DRD4M	Adjustable	10	1000 lm			30	3000K	NS	Narrow Spot (15°) ⁶	W	White ⁷	O	0-10V
		12	1250 lm ⁴			35	3500K	SP	Spot (25°)				
		15	1500 lm ⁴			40	4000K	FL	Flood (40°)				
						3W	Warm Dim ⁵	WF	Wide Flood (60°) ⁴				
								LS	Linear Spread				
								SF	Soft Focus				

M SERIES TRIM

PRODUCT CODE		SHAPE		STYLE		FINISH		OPTION	
<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>		<input type="text"/>	
M4T	4" Trim	R	Round	S	Beveled	WH	White	[Blank]	None
				H	Hyperbolic ⁸	BK	Black	DOF	Decorative: Open, Frosted ^{3,4,10,11,12}
				P	Pinhole ^{3,8}	BZ	Bronze	DCF	Decorative: Closed, Frosted ^{3,4,10,11,12}
				B	Beveled Pinhole ^{3,8}	CW	Clear Diffuse, White Flanged	DCC	Decorative: Closed, Clear, Frosted Side ^{3,4,10,11,12}
				L	Wall Wash ^{2,4,9}	WW	Warm Diffuse, White Flanged	DCCF	Decorative: Closed, Clear, Frosted Inside ^{3,4,10,11,12}
				C	Square Conversion ^{4,10}	CC	Custom Color	FL	Flangeless ^{8,13,15}
								DF	Dead Front ^{4,10,11,14}

M4XRUD	Flangeless Mud Plate <i>(Required for Flangeless Trim drywall installation)</i>
M4KRTEMPLATE	Flangeless Wood Template <i>(Recommended for Flangeless Trim wood installation)</i>

¹ Only available in Standard rating

² Not available for 1500 lm

³ Only available for 750 lm or 1000 lm

⁴ Only available in Fixed module

⁵ Only available in 1000 lm

⁶ Not available in Warm Dim CCT

⁷ Only available for Adjustable module

⁸ Only available in White, Black, Bronze or Custom Color finish

⁹ Only available for Spot beam spread with Warm Dim CCT, Narrow Spot beam spread for all other CCT

¹⁰ Only available in White or Custom Color finish

¹¹ Only available in Beveled style

¹² Only available for General Ambient beam spread

¹³ Not available for Square Conversion or Concrete Construction

¹⁴ Only available for 750 lm

¹⁵ Mudplate is required for all FL trims except for wood ceiling applications