

# LED Cleat™ Track Fixture



## Features

- Solid diecast aluminum fixture
- Integrated driver
- 180° tilt, 358° rotation
- 50,000 hours life-span
- 38° Beam Angle Standard. Optional Lenses: EP719C (15°) or EP720C (24°) available
- This track head comes standard as H Style. J (Juno) and L (Lightolier) styles are available: For J style please order PJTHI (W/B) with the track head.

For L style please order PLTHI (W/B) with the track head.

Note these must be factory installed.

## Specifications

<b>Wattage</b>	10W - 13W
<b>Lumens</b>	700 lm - 1000 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	3000K
<b>Dimmable</b>	Yes
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	38°

## Options



White



Black

## Technical Details

**Construction:** Full diecast construction for exceptional heat management and lasting quality. Powder coat architectural white and architectural black matte finishes.

**Adjustability:** Track head is adjustable 90° tilt with 358° rotation.

**Optics:** Lens provides smooth lumen output at standard 38°. Optional Lenses: EP719C (15°) or EP720C (24°) available.

**Installation:** Effortlessly installed into H-Style track from ELCO or others. Compatible with Single and Double circuit track. Can be special ordered as J-Style (requires PJTLO W/B) or L-Style (requires PLTLO W/B).

### LED Technology:

- Extremely accurate Color Rendering Index of 90+ CRI
- Efficacy of over 81 lumens per watt
- Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results
- Instant On to Full Brightness technology
- Chip on Board LED design results in a smooth lumen output with no LED pixelation

### Dimmability:

- Triac and ELV dimmable down to 10%
- Flicker-Free Dimming
- For full list of dimmers refer to the Dimmer Compatibility List


### Electrical:

- Driver is rated for 120V input
- High Efficiency driver with a power factor > 0.9

**Listings:** ETL Listed. RoHS Compliant

**Warranty:** ELCO Products are built to last. 5-year Limited warranty.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
ET62530DW	LED	700 lm	3000K	10W	120V	Yes	38°	All White
ET62530DB	LED	700 lm	3000K	10W	120V	Yes	38°	All Black
ET62630DW	LED	1000 lm	3000K	13W	120V	Yes	38°	All White
ET62630DB	LED	1000 lm	3000K	13W	120V	Yes	38°	All Black




# Photometric Report

## LED Cleat™ Track Fixture

### PHOTOMETRIC REPORT

Product #: ET62530D  
 Wattage / Lumens: 10W / 706.3 lm  
 Luminaire LPW: 70.6 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	1827
5	1675
15	925
25	305
35	89
45	35
55	15
65	6
75	1
85	0
90	0

### ILLUMINANCE AT A DISTANCE


Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	158	2.1'
6'	55.5	3.1'
8'	28.5	4.3'
10'	19.2	5.3'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	593.6	83.2
0-40°	659.9	92.5
0-60°	704.4	98.7
0-90°	713.1	99.9

### PHOTOMETRIC REPORT

Product #: ET62630D  
 Wattage / Lumens: 13W / 1000 lm  
 Luminaire LPW: 76.9 lm/W



### CANDLE POWER SUMMARY

Degress Vertical	0°
0	2560
5	2348
15	1296
25	428
35	124
45	48
55	21
65	8
75	2
85	1
90	0

### ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Center Beam Footcandles	Beam Diameter
4'	221	2.1'
6'	77.8	3.1'
8'	40.0	4.3'
10'	26.9	5.3'

### ZONAL LUMEN SUMMARY

Zone	Lumens	%Luminaire
0-30°	832.2	83.2
0-40°	925	92.5
0-60°	987.3	98.7
0-90°	999.5	99.9