

# 3" Koto Sylo™ Monopoint



## Features

- Modern Monopoint Die-Cast aluminum fixture for easy maintenance and upgrades
- Includes Standard 38° lens, with 28° and 60° lenses. Optional: 15° and 18° lenses available
- Fits 3 ½" and 4" Octagon and Round Junction boxes
- Sunset option dims from 3000K to 1800K
- 90° tilt, 358° rotation
- Energy Star Certified. Title 24 JA8-2019 Compliant
- Life span of 50,000 hours L70

## Specifications

<b>Wattage</b>	5W - 18W
<b>Lumens</b>	350 lm - 1500 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	2700K - SunsetK
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>Beam Angle</b>	38°
<b>CRI</b>	95+
<b>Damp Location</b>	UL Listed

## Options



All White



All Black



All Silver

## Technical Details

**Optics:** Polycarbonate module lens diffuses light evenly throughout while reducing glare with LED technology.

**Construction:** Integrated driver and light engine with quick connect. Diecast aluminum body with heat fins allows for efficient cooling.

**Installation:** Twist-on design for toolless module installation.

**Electrical:** Module connects to 120V power supply. High-efficiency driver with a power factor >0.9. Start time of less than 0.75 seconds.


**LED Technology:** Extremely accurate Color Rendering Index of 95+. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing integrated heat sink. Instant On to Full Brightness technology. No LED pixelation.

**Dimmability:** For full list of dimmers, refer to the Dimmer Compatibility List. Industry-leading dimming that dims smoothly with no hot spots or flickering.

**Listings:** UL Listed for Damp Locations. RoHS Compliant. Meets Energy Star & California Title 24 JA8-2019 standards.

**Warranty:** ELCO Products are built to last with a 5-year Limited Warranty.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
<b>E36MW-0727</b>	LED	750 lm	2700K	10W	120V	Triac/ELV	38°	All White
<b>E36MB-0727</b>	LED	750 lm	2700K	10W	120V	Triac/ELV	38°	All Black
<b>E36MB-11SD</b>	LED	1150 lm	SunsetK	12.5W	120V	Triac/ELV	38°	All Black
<b>E36MW-11SD</b>	LED	1150 lm	SunsetK	12.5W	120V	Triac/ELV	38°	All White
<b>E36MS-09SD</b>	LED	950 lm	SunsetK	10W	120V	Triac/ELV	38°	Silver
<b>E36MB-09SD</b>	LED	950 lm	SunsetK	10W	120V	Triac/ELV	38°	All Black
<b>E36MW-09SD</b>	LED	950 lm	SunsetK	10W	120V	Triac/ELV	38°	All White
<b>E36MS-11SD</b>	LED	1150 lm	SunsetK	12.5W	120V	Triac/ELV	38°	Silver
<b>E36MS-1140</b>	LED	1150 lm	4000K	12.5W	120V	Triac/ELV	38°	Silver
<b>E36MS-1135</b>	LED	1150 lm	3500K	12.5W	120V	Triac/ELV	38°	Silver
<b>E36MS-1130</b>	LED	1150 lm	3000K	12.5W	120V	Triac/ELV	38°	Silver
<b>E36MS-1127</b>	LED	1150 lm	2700K	12.5W	120V	Triac/ELV	38°	Silver

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
E36MB-1140	LED	1150 lm	4000K	12.5W	120V	Triac/ELV	38°	All Black
E36MB-1135	LED	1150 lm	3500K	12.5W	120V	Triac/ELV	38°	All Black
E36MB-1130	LED	1150 lm	3000K	12.5W	120V	Triac/ELV	38°	All Black
E36MB-1127	LED	1150 lm	2700K	12.5W	120V	Triac/ELV	38°	All Black
E36MW-1140	LED	1150 lm	4000K	12.5W	120V	Triac/ELV	38°	All White
E36MW-1135	LED	1150 lm	3500K	12.5W	120V	Triac/ELV	38°	All White
E36MW-1130	LED	1150 lm	3000K	12.5W	120V	Triac/ELV	38°	All White
E36MW-1127	LED	1150 lm	2700K	12.5W	120V	Triac/ELV	38°	All White
E36MS-0940	LED	950 lm	4000K	10W	120V	Triac/ELV	38°	Silver
E36MS-0935	LED	950 lm	3500K	10W	120V	Triac/ELV	38°	Silver
E36MS-0930	LED	950 lm	3000K	10W	120V	Triac/ELV	38°	Silver
E36MS-0927	LED	950 lm	2700K	10W	120V	Triac/ELV	38°	Silver
E36MB-0940	LED	950 lm	4000K	10W	120V	Triac/ELV	38°	All Black
E36MB-0935	LED	950 lm	3500K	10W	120V	Triac/ELV	38°	All Black
E36MB-0930	LED	950 lm	3000K	10W	120V	Triac/ELV	38°	All Black
E36MB-0927	LED	950 lm	2700K	10W	120V	Triac/ELV	38°	All Black
E36MW-0940	LED	950 lm	4000K	10W	120V	Triac/ELV	38°	All White
E36MW-0935	LED	950 lm	3500K	10W	120V	Triac/ELV	38°	All White
E36MW-0930	LED	950 lm	3000K	10W	120V	Triac/ELV	38°	All White
E36MW-0927	LED	950 lm	2700K	10W	120V	Triac/ELV	38°	All White
E36MS-0740	LED	750 lm	4000K	10W	120V	Triac/ELV	38°	Silver
E36MS-0735	LED	750 lm	3500K	10W	120V	Triac/ELV	38°	Silver
E36MS-0730	LED	750 lm	3000K	10W	120V	Triac/ELV	38°	Silver
E36MB-0740	LED	750 lm	4000K	10W	120V	Triac/ELV	38°	All Black
E36MB-0735	LED	750 lm	3500K	10W	120V	Triac/ELV	38°	All Black
E36MB-0730	LED	750 lm	3000K	10W	120V	Triac/ELV	38°	All Black
E36MW-0740	LED	750 lm	4000K	10W	120V	Triac/ELV	38°	All White
E36MW-0735	LED	750 lm	3500K	10W	120V	Triac/ELV	38°	All White
E36MW-0730	LED	750 lm	3000K	10W	120V	Triac/ELV	38°	All White
E36MS-0727	LED	750 lm	2700K	10W	120V	Triac/ELV	38°	Silver
E36MW-08CT5	LED	825 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	All White
E36MB-08CT5	LED	825 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	All Black
E36MS-08CT5	LED	825 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	Silver
E36MW-10CT5	LED	1000 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	All White
E36MB-10CT5	LED	1000 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	All Black
E36MS-10CT5	LED	1000 lm	2700K, 3000K, 3500K, 4000K, 5000K	10W	120V	Triac/ELV	38°	Silver
E36MW-0327	LED	350 lm	2700KK	5W	120V	Triac/ELV	38°	All White
E36MB-0327	LED	350 lm	2700KK	5W	120V	Triac/ELV	38°	All Black
E36MS-0327	LED	350 lm	2700KK	5W	120V	Triac/ELV	38°	Silver
E36MW-0330	LED	350 lm	3000KK	5W	120V	Triac/ELV	38°	All White
E36MB-0330	LED	350 lm	3000KK	5W	120V	Triac/ELV	38°	All Black
E36MS-0330	LED	350 lm	3000KK	5W	120V	Triac/ELV	38°	Silver
E36MS-1527	LED	1500 lm	2700K	18W	120V	Triac/ELV	38°	Silver
E36MS-155D	LED	1500 lm	SunsetK	18W	120V	Triac/ELV	38°	Silver
E36MS-1540	LED	1500 lm	4000K	18W	120V	Triac/ELV	38°	Silver
E36MS-1535	LED	1500 lm	3500K	18W	120V	Triac/ELV	38°	Silver
E36MS-1530	LED	1500 lm	3000K	18W	120V	Triac/ELV	38°	Silver

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Beam Angle	Finish
E36MB-1527	LED	1500 lm	2700K	18W	120V	Triac/ELV	38°	All Black
E36MB-1540	LED	1500 lm	4000K	18W	120V	Triac/ELV	38°	All Black
E36MB-1535	LED	1500 lm	3500K	18W	120V	Triac/ELV	38°	All Black
E36MB-1530	LED	1500 lm	3000K	18W	120V	Triac/ELV	38°	All Black
E36MB-155D	LED	1500 lm	SunsetK	18W	120V	Triac/ELV	38°	All Black
E36MW-1527	LED	1500 lm	2700K	18W	120V	Triac/ELV	38°	All White
E36MW-1540	LED	1500 lm	4000K	18W	120V	Triac/ELV	38°	All White
E36MW-1535	LED	1500 lm	3500K	18W	120V	Triac/ELV	38°	All White
E36MW-1530	LED	1500 lm	3000K	18W	120V	Triac/ELV	38°	All White
E36MW-155D	LED	1500 lm	SunsetK	18W	120V	Triac/ELV	38°	All White

## Product Number Builder Example: E36MW-0727

Koto Sylo™	Style	Finish	Koto™ Module	Color Temp.	Voltage	Beam Angle
<b>E36</b>	<b>M</b> Monopoint	<b>W</b> All White <b>B</b> All Black <b>S</b> All Silver	<b>-03</b> 350 lm <sup>1,2</sup> <b>-07</b> 750 lm <b>-09</b> 950 lm <b>-11</b> 1150 lm <b>-12</b> 1250 lm <b>-15</b> 1500 lm 825 lm (CT5 <b>-08</b> Option Only) <sup>1,3</sup> 1000 lm (CT5 <b>-10</b> Option Only) <sup>1,3</sup>	<b>27</b> 2700K <b>30</b> 3000K <b>35</b> 3500K <b>40</b> 4000K Sunset (-09 <b>SD</b> and -11 only) <sub>4,5</sub> <b>CT5</b> 2700K - 5000K <sub>6,7</sub>	120V, Triac/ELV <b>D</b> 120/277V, 0-10V/Triac/ELV	38° lens <sup>8</sup> <b>-S</b> 18° lens <b>-N</b> 28° lens <b>-W</b> 60° lens <b>-T</b> 10° lens <sup>1,9</sup>

<sup>1</sup> Available as 120V, Triac/ELV only

<sup>2</sup> Available with 2700 and 3000 Color Temperature Only

<sup>3</sup> Available with CT5 color temperature only

<sup>4</sup> Available with -09 and -11 lumen outputs only

<sup>5</sup> Sunset, Dim to Warm technology, automatically transitions from 3000K to 1800K when dimmed

<sup>6</sup> Available with -08 and -10 lumen outputs only

<sup>7</sup> Available as 120V, Triac/ELV only

<sup>8</sup> Includes 28° and 60° lens in the box

<sup>9</sup> Available with 350 and 750 lumen, 2700K and 3000K options only



**ELCO Lighting**

# Dimmer Compatibility Chart

## Standard Koto™ LED Modules

For ELK07, ELK08CT5, ELK09, ELK10CT5, & ELK11 Series

### For Reference Only

Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards. Consult the dimmer manufacturer prior to installation to ensure compatibility.

Manufacturer	Product	Part Number	Dimmed Light Output Range
Leviton	Decora SureSlide® Single Pole with Slide -to-Off	6672	15% - 100%
	Leviton Dimmer	1K3502	5% - 100%
Lutron	Vive, 120V, 150W LED/CFL, 600W Incandescent/Halogen, FP, Single Pole/Multi-Location Dimmer, Commercial Application	MRF2S-6CL	12% - 91%
	Panel Model, Commercial/Residential Application, FP	GP (Harrier) Card	10% - 94%
	Grafik QS/Mailbox Power Module, 120/220 to 240V AC, LED/Incandescent/Halogen Load Type, Commercial/Residential Indoor Application, FP	LQRJ-WPM-6P	10% - 95%
	Grafik Eye 3000/HomeWorks, 120V, Incandescent/Fluorescent Load Type, Commercial/Residential Application, FP	HWI-WPM-6D-120	10% - 95%
	Panel Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4U-120	10% - 95%
	Panel Adaptive Dimming Module, 120V, Commercial/Residential Application, FP	HW/LP-RPM-4A-120	9% - 95%
	HomeWorks® QS for CFL/LED loads, 120V, RP, Commercial/Residential Application	LQSE-4A1-D/MQSE-4A1-D/ MQSE-3A1/MQSE-2A1-D	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Reverse Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	8% - 95%
	Energi Savr Node LED+ Phase Adaptive, Commercial Application, Forward Phase, (Zone 1) (Zones 2-4)	QSN-4A5-S	10% - 97%
	RadioRA®2, 120V, 50/60-Hz, 150W LED or 600W Incandescent/Halogen, 3-Way & 4-Way, Residential Application	RRD-6CL	10% - 95%
	RadioRA®3, 120V, 250W LED/CFL or 500W Incandescent/Halogen, Single Pole, Multi-Location	RRST-PRO-N	10% - 95%
	HomeWorks® QS, 120V, 60-Hz, 150W LED/CFL or 600W Incandescent/Halogen/MLV, Residential Application	HQRD-6CL(H2) HQRA-6CL(H2)	10% - 95%
	Homeworks QS, Residential Application, Reverse Phase	LQSE-4A-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Reverse Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	8% - 89%
	HomeWorks® for LED/Incandescent/Halogen loads, Forward Phase, (Zone 1) (Zones 2-4)	LQSE-4A5-120-D	10% - 100%
	Ariadni® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	AYCL-153P	10% - 100%
	Skylark Contour® C-L, Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	CTCL-153P	10% - 100%
Skylark® C-L Single Pole/3-Way, 150W LED/CFL or 600W Incandescent/Halogen	SCL-153P	10% - 100%	

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com

Manufacturer	Product	Part Number	Dimmed Light Output Range
Lutron	Diva® Series 150W Single Pole/3-Way Dimmer	DVCL-153P	10% - 100%
	Skylark Contour® Single Pole/3-Way 1000W Incandescent/Halogen	CT-103P	10% - 100%
	Skylark® Single Pole 300W ELV Preset Dimmer	SELV-300P	5% - 100%
	Skylark® Single Pole 600W Incandescent/Halogen, Slide-to-Off Dimmer	S-600P	5% - 100%
	Diva® 300W Single Pole/3-Way ELV Dimmer	DVELV-303P	10% - 100%
	Diva® 600W Single Pole Incandescent/Halogen Preset Dimmer	DV-600P	5% - 100%
	Ariadni® 600W Single Pole Magnetic Low Voltage Dimmer	AYLV-600P	5% - 100%
	Ariadni® 600W Single Pole/3-Way Incandescent/Halogen Dimmer	AY-603P	5% - 100%
	Maestro® 600W Single Pole/3-Way ELV Dimmer	MAELV-600	5% - 100%
	Maestro® C-L Single Pole/3-Way Dimmer. 150W Max for LED/CFL or 600W Max for Incandescent/Halogen	MACL-153M	10% - 100%
	Caséta® Wireless Dimmer	PD-6WCL	10% - 100%

**\*NOTE: Refer to dimmer manufacturer's documentation for installation instructions and circuit details**

Disclaimer: Minimum and maximum loads for LEDs and CFLs are given in number of lamps and may vary depending on the lamp being used. Testing conducted by ELCO Lighting is not a substitute for and does not imply certification by an independent laboratory or any other standards certification. Refer to manufacturer specifications for more detailed information on product certifications and standards.

Integrating our lighting with your Smart Home System is a breeze. Simply check your Smart Home system for compatible smart switches and cross reference that with our Dimming Compatibility Chart. Once the switches are integrated with your Smart Home system your lights will be ready to go.



2042 E. Vernon Ave. Vernon CA 90058 Tel 323.231.2600 Fax 323.231.3200 elcolighting.com