

4" 0-10V LED Inserts with 5-CCT and 3-Lumen Switch

This unique Ply System 0-10V dimmable LED Insert gives you the options you are looking for in one fixture. Engineered with energy-efficient LED technology and with a 120/277V 0-10V dimmable driver for a budget friendly 0-10V solution. Switch to desired Color Temperature (2700K, 3000K, 3500K, 4000K or 5000K) and Lumen Output (850 lm, 1000 lm, 1500 lm) by using manual switch located on module. Designed to be used for New Construction, Remodel with ELCO Ply™ System Housings or as a retrofit with existing housings.



Features

- Manual switch to choose desired Color Temperature and Lumen Output
- 0-10V Dimmable
- 120/277V Driver
- Soft white lens provides smooth lumen distribution and eliminates LED pixelation
- Deep set LED trim reduces glare while providing even illumination
- 90+ CRI for extremely accurate color rendering
- CA Title 24, ETL listed, ENERGY STAR, JA8-2016-E
- Life span of 50,000 hours L70
- Patent Pending

Specifications

Wattage	9.5, 13.5, 18W
Lumens	850, 1000, 1500 lm
Voltage	120/277V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	0-10V
Lamp Type	LED
CRI	90+
Wet Location	Listed

Options



All White




All Black



Haze/White Ring

Dimensions



Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly while reducing glare with LED technology.

Construction: For use in IC and non-IC applications. High quality powder coat prevents rust and cracking.

Installation: For use with ELCO 4" Ply™ Housings EL49FICDXA, EL49FICDXA-B, EL490ICDXA, EL490ICDXA-B, EL490ICDXA-EM5, EL490ICDXA.

Electrical: 120/277V Input. Power factor > 0.9 Start time of less than .75 seconds.

LED Technology: Extremely accurate color rendering with 93+ CRI. Lumen Maintenance of 50,000 hours L70 Life based on LM80 standardized test results. Superior Thermal Management by utilizing heat sink. Instant On to Full Brightness. No LED pixelation.

Dimmability: Works with 0-10V dimmers. Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List. Dims with no hot spots or flickering.

Listings: UL Listed for Wet Location. RoHS Compliant. ENERGY STAR® Certified. California Title 24 JA8-2016-E.

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EL475CT5DW	LED	850,	2700K,	9.5,	120/277V	0-10V	All White
		1000,	3000K,	13.5,			
		1500 lm	3500K, 4000K, 5000K	18W			
EL475CT5DH	LED	850,	2700K,	9.5,	120/277V	0-10V	All Haze
		1000,	3000K,	13.5,			
		1500 lm	3500K, 4000K, 5000K	18W			
EL475CT5DBB	LED	850,	2700K,	9.5,	120/277V	0-10V	All Black
		1000,	3000K,	13.5,			
		1500 lm	3500K, 4000K, 5000K	18W			
EL475CT5DHW	LED	850,	2700K,	9.5,	120/277V	0-10V	Haze/White Ring
		1000,	3000K,	13.5,			
		1500 lm	3500K, 4000K, 5000K	18W			

Product Number Builder

Example: **EL475CT5DW**

ELCO 4" LED Inserts

EL475

Color Temp.

CT5 2700K-5000K


Finish

DW All White
DBB All Black
DH All Haze
DHW Haze/White Ring


Compatible Products

For use with 4" 0-10V LED Inserts with 5-CCT and 3-Lumen Switch


4" 0-10V Dedicated LED Housings



4" 0-10V Dedicated LED Housing
New Construction



4" 0-10V Dedicated LED Housing
Remodel



2-Hour Fire Rated
4" 0-10V Dedicated LED Housing
New Construction

CAT NO.	SPECIFICATIONS
EL490ICDXA	14W, 120/277V
EL490ICDXA-B	Butterfly Bracket
EL490ICDXA-EM5	Emergency Back-Up

CAT NO.	SPECIFICATIONS
EL490RICDXA	14W, 120/277V

CAT NO.	SPECIFICATIONS
EL49FICDXA	7 3/4" Height - 14W, 120/277V
EL49FICDXA-B	Butterfly Bracket


4" Accessories



Hanger Bars
for Butterfly Bracket



Hanger Bars
for Butterfly Bracket



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
FB27	Set of two 27" flat hanger bars for wood construction

CAT NO.	SPECIFICATIONS
CH26	Set of two 26" C-Channel hanger bars for T-Bar ceiling

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V