



## S-Line: Bullet Flood Light

3-CCT Selectable



### Detail Specification:

- Finish: Bronze or White
- IP Rating: Wet Location
- Beam Angle: 40°
- CCT: 30/40/50K Selectable
- Lumens: 3,500
- Chip: SMD 2835, R9 >50, CRI >80
- Operating Temperature: -4° - 122° F
- Lens: PC Lens: Clear acrylic with optics
- Average life (L70) of 70,000 hours

### Applications:

- Landscape
- Walkways & Pathways
- Security Lighting
- Hospitality, Multi-Family
- Outdoor Corridors
- General Outdoor Lighting
- Residential, Commercial and Industrial

### Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Compatible with on/off and bi-level motion sensors
- Select-n-Switch Technology
- Instant-On to full brightness

### Driver Options:

- UNV: 120-277V 0-10V Dimmable
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

### Mounting & Installation:

- 1/2" Knuckle Mount
- Adjustable 180°
- Cord: #18 AWG stranded wires

### Certifications:

- UL Listed for USA and CA
- DLC Listed
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

### Series

**LED-BLT-25W-TRI-BZ-KN-UNV**

Bronze Finish

**LED-BLT-25W-TRI-WH-KN-UNV**

White Finish

*Specs and model numbers are subject to change with or without notice.*

**FEATURES**



**DIMENSIONS**

