

BR SERIES: 5-CCT LED BULBS

BR-20, BR-30, BR-40






BR-20



BR-40



BR-30



Detail Specifications

- IP Rating: Damp Location
- Beam Angle: 110°
- 5-CCT: 27/30/35/40/50K
- Chip: SMD 2835, R9 >50, CRI >90
- Operating Temperature: -4° - 114° F
- Average life (L70) of 25,000 hours

Applications:

- Can Lights
- Interior Lighting
- Downlighting
- Showcases
- Residential, Commercial and Industrial

Product Information:

- Suitable for use in existing fixtures
- Instant-On to full brightness

Driver Options:

- 120V
- Triac Dimmable
- PF >0.9, 50/60Hz

Mounting & Installation:

- E26 Socket
- Direct BR Lamp Replacement

Packaging:

- All bulbs come in individual color boxes, but are sold in inner carton qty packs only

Carton Qty.	BR-20	BR-30	BR-40
Inner Carton	10	6	6
Master Carton	100	48	48

Certifications:

- ETL Listed for USA and CA
- Energy Star
- Title 20 and JA8-2022 Approved
- 3 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017

Dimmer List:

Leviton	6674
Lutron	LGCL-153P
Lutron	DVCL-153P
Lutron	CTCL-153P
Lutron	MAELV-300

Series

LED-BR20-6W-5CCT

450 Lumens 50W Equivalent

LED-BR30-8.5W-5CCT

650 Lumens 75W Equivalent

LED-BR40-13W-5CCT

1,050 Lumens 100W Equivalent

Specs and model numbers are subject to change with or without notice.