

# Full Cut Off Wall Packs Adjustable: AFC-Line

## Adjustable Lens



### Detail Specifications

- Finish: Bronze, Black, White, Custom finishes available
- IP Rating: Wet Location
- Impact Rating: IK08
- Beam Angle: 90x110°
- Chip: SMD 2835, R9 >50, CRI >80
- BUG:
  - 30W: B2-U2-G1
  - 5P50W: B3-U3-G1
  - 5P80W: B3-U3-G1
- Operating Temperature: -40° - 122° F
- Lens: Clear acrylic with optics
- Average life (L70) of 70,000 hours

### Applications:

- Walkways & Pathways
- Parking Lots
- Hospitality, Multi-Family
- Outdoor Corridors
- Residential, Commercial and Industrial

### Product Information:

- Sturdy die-cast aluminum housing finished with corrosion free powder coat
- Full Cut-Off Dark Sky Compliant
- Photocell is included with an easy quick disconnect
- Instant-On to full brightness
- Select-n-Switch Technology: 3-CCT + 3-Power Selectable (30w is single power)

### Driver Options:

- UNV: 120-277V 0-10V Dimmable
- HV: 277-480V 0-10V Dimmable
- Built in 6Kv Surge Protector
- THD: <20% (+/-5% tolerance), PF >0.9, 50/60Hz

### Mounting & Installation:

- Five 1/2" knockouts: 1 one each side for convenient installation

### Certifications:

- UL Listed for USA and CA
- DLC Listed
- ROHS Compliant
- Approved for CA T24
- 5 Year Limited Warranty
- FCC CFR 47, GCC Part 15, Subpart B:2017


Series	Finish <sup>1</sup>	Photocell	Voltage	Sensor <sup>2</sup>	Emergency	Surge Protector	Optional Accessories (Order Separately)
<b>LED-WPFC-ADJ-30W-TRI</b> 30W • 30/40/50K	<b>BZ</b> Bronze (Standard)	<b>(blank)</b> No	<b>(blank)</b> 120-277V	<b>(blank)</b> No Sensor	<b>(blank)</b> No Emergency	<b>(blank)</b> 6KV Built in	<b>Remote for Sensors</b>
<b>LED-WPFC-ADJ-3P50W-TRI</b> 30/40/50W • 30/40/50K	<b>BL</b> Black	<b>PC</b> Photocell	<b>HV</b> 277-480V	<b>BMS</b> Bi-Level Motion + Daylight Sensor (S-BMS-EXT-1)	<b>EMB</b> Emergency Backup	<b>20KV</b> 20KV Surge Protector	<b>S-LINE-R</b> S-Line Remote
<b>LED-WPFC-ADJ-3P80W-TRI</b> 60/70/80W • 30/40/50K	<b>WH</b> White <b>GRY<sup>1</sup></b> Gray <b>CS<sup>1</sup></b> Custom Color	<b>Button</b> Photocell		<b>BMSBT</b> Bi-Level Motion + Daylight Sensor -Bluetooth Control- (S-BMS-EXT-1-BT) (HB01DMS-C)			

1. Standard quickship is bronze. Other colors are custom finishes


2. Sensors require remote for programming

Specs and model numbers are subject to change with or without notice.


**FEATURES**





**DIMENSIONS**



**3P50W**



**3P80W**





**S-LINE-R**



**S-BMS-EXT-1**  
**S-BMS-EXT-1-BT**

**WALL PACK**

Model	Voltage	Watts	Lumens	Color	CRI
LED-WPFC-ADJ-30W-TRI-BZ	120-277V	30W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P50W-TRI-BZ	120-277V	30/40/50W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P50W-TRI-BL	120-277V	30/40/50W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P50W-TRI-WH	120-277V	30/40/50W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P80W-TRI-BZ	120-277V	60/70/80W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P80W-TRI-BL	120-277V	60/70/80W	145LM/W	30/40/50k	>80
LED-WPFC-ADJ-3P80W-TRI-WH	120-277V	60/70/80W	145LM/W	30/40/50k	>80

**REMOTE CONTROL**

Accessory Model	Description
S-LINE-R	Remote for S-LINE Series Sensors

**HB-LINE-SENSORS**

Model	Item Description	Voltage	Watts
S-BMS-EXT-1	S-Line: Bi Level Motion Sensor w/ Daylight Harvesting, Ideal for use with LED WALLPACKS. 12V Aux REQD. (Remote Required)	12V	<1w
S-BMS-EXT-1-BT	S-Line: Bi Level Motion Sensor w/ Daylight Harvesting, Ideal for use with Wallpacks. 12V Aux REQD. (Remote Required)	12V	<1w