

Product Features:

- Smallest Form Factor in Mogul-Base Category
- Integrated 4kA/4kV Surge Protection
- Step-Down Thermal Management Protection
Wattage step-down circuit automatically prevents overheating due to high increases in ambient temperatures. Wattage returns to normal as temperatures decrease.
- Omni-directional
- Rated for Fully Enclosed Fixtures
- Wet Location Approved
- Special Adapter Transforms Base from E26 to E39
- Direct Retrofit for HID & CFL Fixtures
- Heat and Impact Resistant
- UV Protected Optical Grade Lens
- Fully Enclosed and Shatterproof
- Highly Resistant to Shock and Vibration

Product Specifications:

Wattage: 120 Watts
 Selectable Kelvin: 3000K—4000K—5000K
 Lumens: Up to 15,600lm
 Efficacy: Up to 130 lm/W
 CRI: >80
 Input Voltage: 120–277 VAC
 Power Factor: >0.95
 Operating Temperature: -40°F to 140°F (-40°C to 60°C)
 Operational Lifetime: 50,000 Hours
 Beam Angle: 300°
 Base Type: EX39
 Total Harmonic Distortion (THD): < 20%
 Dimensions: 5.12"Ø x 11.26"

Project: _____

Date: _____

Catalog #: _____

Notes: _____



SELECTABLE KELVIN
3000K, 4000K or 5000K

Available Accessories:



Daylight / Occupancy
ESL-3DHOC-LV



No Fans



No Noise



No Bugs



SHATTERPROOF



Ordering Guide:

ESL	TYPE	WATTAGE	GENERATION	SELECTABLE KELVIN	BASE
ESL	CL (CL) Corn Light	120W 120 Watts	5 (5) 5th Generation	3050 (3050) 3000K—4000K—5000K	(EX39) EX39

Catalog Data:

ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	SELECTABLE KELVIN
ESL-CL-36W-53050-S-M ESL-CL-36W-53050-EX39	36	4,680	130	3000K—4000K—5000K
ESL-CL-46W-53050-S-M ESL-CL-46W-53050-EX39	46	5,980	130	3000K—4000K—5000K
ESL-CL-55W-53050-S-M ESL-CL-55W-53050-EX39	55	7,150	130	3000K—4000K—5000K
ESL-CL-80W-53050-EX39	80	10,400	130	3000K—4000K—5000K
ESL-CL-120W-53050-EX39	120	15,600	130	3000K—4000K—5000K

Product Dimensions:

