

### Key Features & Benefits:

- 5CCT Field Adjustable
- Compatible with 3" and 4" J Boxes
- Wet Location Rated
- 120V Triac Dimmable
- T24 Compliant
- Easy Surface Mount Installation
- Optional Trim Color Kits\*


### Product Specifications:

Wattage: 20 Watts  
 Selectable Kelvin: 2700K, 3000K, 3500K, 4000K, 5000K  
 Lumen Output: Up to 1,492 Lumens  
 Efficacy: Up to 81 lm/W  
 Input Voltage: 120 VAC  
 CRI: >90  
 Battery Life: 90 Minutes  
 Operational Lifetime: 50,000 hrs  
 Dimensions: 9.08" x 9.08" x H 1.18"

Project: \_\_\_\_\_ Date: \_\_\_\_\_  
 Catalog #: \_\_\_\_\_  
 Notes: \_\_\_\_\_



**Integrated Battery Backup with Easily Replaceable Quick Connect Battery**



**Easy Select Kelvin Switch on Backplate**



### Ordering Guide:

ESL	-	TYPE	-	SIZE	-	WATTS	-	GENERATION	-	SELECTABLE KELVIN	-	EMG
ESL	-	DDSK	-	S9	-	20W	-	1	-	2750	-	EMG
		(DDSK) Decorative Disk		(S9) Square 9"		(20W) 20 Watts		(1) 1st Generation		(2750) 2700K, 3000K, 3500K, 4000K, 5000K		

### FIELD INSTALLED ACCESSORIES

ESL-DDSK1-R5-Tff	5" DDSK field installable round trim kit*
ESL-DDSK1-S5-Tff	5" DDSK field installable square trim kit*
ESL-DDSK1-R7-Tff	7" DDSK field installable round trim kit*
ESL-DDSK1-S7-Tff	7" DDSK field installable square trim kit*
ESL-DDSK1-R9-Tff	9" DDSK field installable round trim kit*
ESL-DDSK1-S9-Tff	9" DDSK field installable square trim kit*
ESL-DDSK1-R11-Tff	11" DDSK field installable round trim kit*
ESL-DDSK1-S11-Tff	11" DDSK field installable square trim kit*

Finishes: (ff)=(MW) Field Paintable, (BK) Black, (BN) Brushed Nickel, (BZ) Bronze, (CP) Copper

\*Contact ESL Representative for more information regarding Trim Kit lead times.

### Catalog Data:

#### LED DECORATIVE DISK—TRIAC DIMMING

ITEM#	WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/w)	CRI	INPUT VOLTAGE	DIMENSIONS		
<b>5" ROUND</b>		2700K	704	62	90	120 VAC	Ø 5.61" x H 1.18"		
ESL-DDSK-R5-11W-12750	11W	3000K	752	67					
		3500K	785	69					
		4000K	792	70					
		5000K	784	69					
<b>5" SQUARE</b>		2700K	670	59	90	120 VAC	5.59" x 5.59" x H 1.18"		
ESL-DDSK-S5-11W-12750	11W	3000K	716	64					
		3500K	733	66					
		4000K	735	65					
ESL-DDSK-S5-11W-12750	11W	5000K	727	65					
		<b>7" ROUND</b>		2700K	900	64	90	120 VAC	Ø 7.11" x H 1.18"
		ESL-DDSK-R7-14W-12750	14W	3000K	962	69			
				3500K	1004	72			
4000K	1035			74					
5000K	1004			73					
ESL-DDSK-R7-14W-12750-EMG	14W	2700K	1078	78					
		3000K	1143	84					
		3500K	1196	88					
		4000K	1219	91					
ESL-DDSK-R7-14W-12750-EMG	14W	5000K	1222	89					

Catalog Data:

LED DECORATIVE DISK—TRIAC DIMMING

ITEM#	WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/w)	CRI	INPUT VOLTAGE	DIMENSIONS
<b>7" SQUARE</b>		2700K	862	62			
		3000K	914	66			
ESL-DDSK-S7-14W-12750	14W	3500K	946	69	90	120 VAC	7.09" x 7.09" x H 1.18"
		4000K	938	68			
		5000K	923	68			
<b>7" SQUARE</b>		2700K	1,027	75			
		3000K	1,092	81			
ESL-DDSK-S7-14W-12750-EMG†	14W	3500K	1,159	87	90	120 VAC	7.09" x 7.09" x H 1.18"
		4000K	1,196	89			
		5000K	1,199	88			
<b>9" ROUND</b>		2700K	1,396	71			
		3000K	1,476	75			
ESL-DDSK-R9-20W-12750	20W	3500K	1,568	80	90	120 VAC	Ø 9.08" x H 1.18"
		4000K	1,576	80			
		5000K	1,569	80			
<b>9" ROUND</b>		2700K	1,558	78			
		3000K	1,646	83			
EESL-DDSK-R9-20W-12750-EMG	20W	3500K	1,715	89	90	120 VAC	Ø 9.08" x H 1.18"
		4000K	1,746	89			
		5000K	1,738	89			
<b>9" SQUARE</b>		2700K	1,396	71			
		3000K	1,476	75			
ESL-DDSK-S9-20W-12750	20W	3500K	1,568	80	90	120 VAC	9.06" x 9.06" x H 1.18"
		4000K	1,576	80			
		5000K	1,569	80			
<b>9" SQUARE</b>		2700K	1,371	72			
		3000K	1,437	77			
ESL-DDSK-S9-20W-12750-EMG†	20W	3500K	1,492	81	90	120 VAC	9.06" x 9.06" x H 1.18"
		4000K	1,512	81			
		5000K	1,470	78			
<b>11" ROUND</b>		2700K	1,768	71			
		3000K	1,866	75			
ESL-DDSK-R11-25W-12750	25W	3500K	2,005	81	90	120 VAC	Ø 11.05" x H 1.18"
		4000K	2,009	81			
		5000K	2,004	81			
<b>11" SQUARE</b>		2700K	1,760	71			
		3000K	1,887	76			
ESL-DDSK-S11-25W-12750	25W	3500K	1,966	80	90	120 VAC	11.02" x 11.02" x H 1.18"
		4000K	1,924	79			
		5000K	1,874	79			

†Contact your representative for lead times



Catalog Data:

### LED DECORATIVE DISK—DUAL DIMMING MULTI-VOLT

ITEM#	WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/w)	CRI	INPUT VOLTAGE	DIMENSIONS
<b>5" ROUND MULTI-VOLT</b>		2700K	883	81			
		3000K	917	85			
ESL-DDSK-R5-11W-12750-MV	11W	3500K	953	90	90	120-277V	Ø 5.61" x H 1.18"
		4000K	963	90			
		5000K	953	88			
<b>5" SQUARE MULTI-VOLT</b>		2700K	701	65			
		3000K	738	70			
ESL-DDSK-S5-11W-12750-MV	11W	3500K	772	74	90	120-277V	5.59" x 5.59" x H 1.18"
		4000K	785	75			
		5000K	767	72			
<b>7" ROUND MULTI-VOLT</b>		2700K	1,135	84			
		3000K	1,203	91			
ESL-DDSK-R7-14W-12750-MV	14W	3500K	1,241	94	90	120-277V	Ø 7.11" x H 1.18"
		4000K	1,273	98			
		5000K	1,264	95			
		2700K	1,145	85			
		3000K	1,204	92			
ESL-DDSK-R7-14W-12750-MV-EMG	14W	3500K	1,255	98	90	120-277V	Ø 7.11" x H 1.18"
		4000K	1,273	96			
		5000K	1,267	97			
<b>7" SQUARE MULTI-VOLT</b>		2700K	980	73			
		3000K	1,039	78			
ESL-DDSK-S7-14W-12750-MV	14W	3500K	1,078	83	90	120-277V	7.09" x 7.09" x H 1.18"
		4000K	1,088	83			
		5000K	1,058	79			
		2700	1007	73			
		3000	1085	80			
ESL-DDSK-S7-14W-12750-MV-EMG†	14W	3500	1132	85	90	120-277V	7.09" x 7.09" x H 1.18"
		4000	1148	86			
		5000	1126	83			
<b>9" ROUND MULTI-VOLT</b>		2700K	1,660	88			
		3000K	1,735	93			
ESL-DDSK-R9-20W-12750-MV	20W	3500K	1,789	97	90	120-277V	Ø 9.08" x H 1.18"
		4000K	1,854	101			
		5000K	1,843	99			
		2700K	1,665	86			
		3000K	1,750	93			
ESL-DDSK-R9-20W-12750-MV-EMG†	20W	3500K	1,832	98	90	120-277V	Ø 9.08" x H 1.18"
		4000K	1,869	98			
		5000K	1,864	98			

†Contact your representative for lead times

\*Accessories Sold Separately

Copyright © 2023 ESL Vision, LLC. All rights reserved. Rev. 05/16/23


**Catalog Data:**

**LED DECORATIVE DISK—DUAL DIMMING MULTI-VOLT**

ITEM#	WATTAGE	SELECTABLE KELVIN	MAX LUMEN OUTPUT	MAX EFFICACY (lm/w)	CRI	INPUT VOLTAGE	DIMENSIONS
<b>9" SQUARE MULTI-VOLT</b>		2700K	1,462	80			
		3000K	1,542	86			
ESL-DDSK-S9-20W-12750-MV†	20W	3500K	1,608	91	90	120-277V	9.06" x 9.06" x H 1.18"
		4000K	1,616	91			
		5000K	1,571	86			
<b>9" SQUARE MULTI-VOLT</b>		2700	1329	72			
		3000	1395	77			
ESL-DDSK-S9-20W-12750-MV-EMG†	20W	3500	1461	82	90	120-277V	9.06" x 9.06" x H 1.18"
		4000	1485	83			
		5000	1458	80			
<b>11" ROUND MULTI-VOLT</b>		2700K	2147	94			
		3000K	2249	100			
ESL-DDSK-R11-25W-12750-MV†	25W	3500K	2315	104	90	120-277V	Ø 11.05" x H 1.18"
		4000K	2367	106			
		5000K	2343	103			
<b>11" SQUARE MULTI-VOLT</b>		2700	2024	87			
		3000	2126	93			
ESL-DDSK-S11-25W-12750-MV†	25W	3500	2210	98	90	120-277V	11.02" x 11.02" x H 1.18"
		4000	2245	99			
		5000	2207	95			

†Contact your representative for lead times

**Dimensions:**



ITEM#	DIMENSIONS			WEIGHT (LBS)
	A	B	C	
<b>5" ROUND</b>				
ESL-DDSK-R5-11W-12750	Ø 5.61"	-	1.18"	0.57
ESL-DDSK-R5-11W-12750-MV	Ø 5.61"	-	1.18"	0.57
<b>5" SQUARE</b>				
ESL-DDSK-S5-11W-12750	5.59"	5.59"	1.18"	0.66
ESL-DDSK-S5-11W-12750-MV	5.59"	5.59"	1.18"	0.66
<b>7" ROUND</b>				
ESL-DDSK-R7-14W-12750	Ø 7.11"	-	1.18"	0.77
ESL-DDSK-R7-14W-12750-EMG	Ø 7.12"	-	1.18"	1.54
ESL-DDSK-R7-14W-12750-MV	Ø 7.11"	-	1.18"	0.88
ESL-DDSK-R7-14W-12750-MV-EMG	Ø 7.12"	-	1.18"	1.65
<b>7" SQUARE</b>				
ESL-D DSK-S7-14W-12750	7.09"	7.09"	1.18"	0.93
ESL-DDSK-S7-14W-12750-EMG	7.09"	7.09"	1.18"	1.87
ESL-DDSK-S7-14W-12750-MV	7.09"	7.09"	1.18"	1.87
ESL-DDSK-S7-14W-12750-MV-EMG	7.09"	7.09"	1.18"	1.87
<b>9" ROUND</b>				
ESL-DDSK-R9-20W-12750	Ø 9.08"	-	1.18"	1.04
ESL-DDSK-R9-20W-12750-EMG	Ø 9.06"	-	1.18"	1.87
ESL-DDSK-R9-20W-12750-MV	Ø 9.06"	-	1.18"	1.34
ESL-DDSK-R9-20W-12750-MV-EMG	Ø 9.06"	-	1.18"	1.87
<b>9" SQUARE</b>				
ESL-DDSK-S9-20W-12750	9.06"	9.06"	1.18"	1.32
ESL-DDSK-S9-20W-12750-EMG	9.06"	9.06"	1.18"	2.29
ESL-DDSK-S9-20W-12750-MV	9.06"	9.06"	1.18"	1.32
ESL-DDSK-S9-20W-12750-MV-EMG	9.06"	9.06"	1.18"	1.32
<b>11" ROUND</b>				
ESL-DDSK-R11-25W-12750	Ø 11.05"	-	1.18"	1.43
ESL-DDSK-R11-25W-12750-MV	Ø 11.05"	-	1.18"	1.43
<b>11" SQUARE</b>				
ESL-DDSK-S11-25W-12750	11.02"	11.02"	1.18"	1.43
ESL-DDSK-S11-25W-12750-MV	11.02"	11.02"	1.18"	1.43

### DDSK Compatible Dimmers:

#### NON-EMG TRIAC DDSK COMPATIBLE DIMMERS

Lutron DVCL-153P

---

Lutron LECL-153PH

---

Lutron LECL-153PH

---

Lutron CTCL-153PH

---

Leviton 6672

---

Leviton 6674

---

Leviton IPSD6

---

Leviton DSL06

---

Leviton IPL06

---

Leviton DSM10

---

#### EMG TRIAC DDSK COMPATIBLE DIMMERS

Lutron DVCL-153P

---

Lutron DVCL-303

---

Lutron LECL-153PH

---

Lutron CT-600P

---

Lutron CTCL-153PH

---

Leviton 6672

---

Leviton 6674

---

Leviton DSL06

---

Leviton IPL06

---

Leviton DSM10

---

Leviton PD-6WCL

---

### DDSK-MV Compatible Dimmers:

#### REGULAR AND EMG TRIAC DDSK COMPATIBLE DIMMERS

Lutron DVCL-153P Diva

---

Lutron DVWCL-153PH Diva

---

Lutron LECL-153PH-WH Lunea

---

Lutron TGCL-153PH

---

Lutron CTCL-153PH Skylark

---

Leviton 6672

---

Leviton 6674

---

Leviton IPSD6

---

Leviton DSL06

---

Leviton IPL06

---

Leviton DSM10

---

Cooper TAL06P-C2

---

