

Key Features & Benefits:

- Housing:
 - 5VA UV protected fiberglass housing
 - Silicone perimeter gasket
 - Stainless steel mounting brackets
- Lens:
 - Clear 100% impact modified acrylic
 - UV stabilized lens
 - Clear polycarbonate clips
- Gear Trey:
 - Pre-painted cold rolled steel
 - Easy access for quick installation
 - Secured with stainless steel wire
- Long Life:
 - 10 year warranty (12 hour run times)
 - 7 year warranty (24 hour run times)
- Ingress IP66 - Suitable for wet locations
- Control Options:
 - Photocell
 - Occupancy
- Emergency capable
- 1/2" NPT / M20 fittings on both sides



Project: _____

Date: _____

Catalog #: _____

Notes: _____



Electrical Data:


Light Specifications:

Lumen Output: Up to 2,220 Lumens
 Efficacy (lm/W): Up to 111 Lumens per Watt
 Kelvin: 3000K, 3500K, 4000K, 5000K
 Color Rendering Index (CRI): >82
 Rated Life: > 80,000 hrs


Driver Data:

Input Voltage: 120-277 VAC
 Input Power: 20W
 Input Current @ 120V: 0.167 Amps
 Input Current @ 240V: 0.083 Amps
 Input Current @ 277V: 0.072 Amps
 Total Harmonic Distortion (THD): <10%
 Power Factor: >0.99
 Operating Temperature: -4 ~ 122°F

Double Ti
Normal Distribution



Double Ti
Wide Distribution



* Made in the USA option available upon request

Catalog Data:

	ITEM#	WATTS	LUMEN OUTPUT	EFFICACY (lm/W)	KELVIN
NARROW DISTRIBUTION	ESL-TI-VP2N-S-20W-F30	20W	2,100	105	3000K
	ESL-TI-VP2N-S-20W-F35	20W	2,100	105	3500K
	ESL-TI-VP2N-S-20W-F40	20W	2,160	108	4000K
	ESL-TI-VP2N-S-20W-F50	20W	2,220	111	5000K
WIDE DISTRIBUTION	ESL-TI-VP2W-S-20W-F30	20W	2,100	105	3000K
	ESL-TI-VP2W-S-20W-F35	20W	2,100	105	3500K
	ESL-TI-VP2W-S-20W-F40	20W	2,160	108	4000K
	ESL-TI-VP2W-S-20W-F50	20W	2,220	111	5000K

Ordering Guide: Example Part Number: ESL-TI-VP2W-S-20W-F40



Additional Options:

- **Emergency:**
 - ESL-EMG-FDC-9.5W (Emergency Backup, 1100 Lumens, 90 Min)
 - **Cord Sets:***
 - ESL-CS3W-6 (Cord Set, White, 3 wire, 6 foot)
 - ESL-CS3W-6P (Cord Set, White, 3 wire, 6 foot, Standard Plug)
 - ESL-CS3W-6TL (Cord Set, White, 3 wire, 6 foot, Twist lock Plug)
 - ESL-CS3W-12 (Cord Set, White, 3 wire, 12 foot)
 - ESL-CS3W-12P (Cord Set, White, 3 wire, 12 foot, Standard Plug)
 - ESL-CS3W-12TL (Cord Set, White, 3 wire, 12 foot, Twist lock Plug)
 - **Latches:**
 - ESL-VPSS (Stainless Steel Latches)
 - **Miscellaneous:**
 - ESL-SPD-277-1 (Surge Protector; 100-277V)
 - ESL-480V-SD01 (480 Volt Step Down Transformer)
 - **Sensors & Controls:**
 - ESL-4OCC (Microwave Occupancy Sensor)
 - ESL-4OCP (Photocell & Microwave Occupancy Sensor)
 - ESL-4OPH (Photocell)
 - ESL-3OCC (IP65 High Bay 0-10v Dimming Sensor)
 - ESL-REM100 (Remote for EL-3OCC)
 - ESL-REM101 (Remote for ESL-4OCC, 4OCP, 4OPH)
 - **Mounting:**
 - ESL-VP-CM-VP4X (Direct Mount to the Ceiling for the 2',4',8' Narrow and Wide Body Fixture - 2 per)
 - ESL-VP-45DM-VP4X (45 Degree Mount for the 2',4',8' Narrow and Wide Body Fixture - 2 per)
- *Other lengths and black cord available upon request

Dimensions:

