


In-Wall Timer - 24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White

Item E1010



PRODUCT DESCRIPTION

These Heavy-Duty In-Wall Timers are ideal for turning on lights, fans, pumps and other heavy duty loads for energy savings, security and convenience. The timer provides up to 12 ON and 12 OFF operations per day.

FEATURES

- ▶ E1010 includes one ON/OFF permanently attached tripper for single ON/OFF control per 24-hour period
- ▶ E1020 includes two ON/OFF trippers and can accommodate up to 12 ON/OFF trippers
- ▶ Programmable in 30-minute intervals
- ▶ Turns ON/OFF heavy-duty loads for energy savings, security and convenience
- ▶ Mounts to any standard junction box
- ▶ Requires neutral connection

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	E1010
Description	24-Hour Heavy-Duty Mechanical In-Wall Timer, 125VAC, 15 A, Permanent Trippers, White
UPC Code	078275440005
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	30 min
Maximum ON/OFF Operations	1
Operation Mode	24 hour
Mechanism Type	Analog/Mechanical
Application Compatibilities	Incandescent; Fluorescent; CFL

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.25 x 3.25 x 1.375 in
-----------------------------------	------------------------

Material Specifications

Color	White
Includes Wall Plate	Yes

Load Ratings

Resistive Load Ratings Ranges	15 A, 125 VAC, 60 Hz
-------------------------------	----------------------

Motor Load Ratings Ranges	12 FLA @ 125 VAC, 60 Hz
Incandescent Load Ratings (Single-Gang)	1500 W, 125 VAC, 60 Hz
Incandescent Single Gang Load Ratings Ranges	1500 W, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	-4 - 77 °F / -20 - 25 °C
-------------------------	--------------------------

Packaging

Unit Carton Dimensions (H x W x D) in	3.251 x 3.501 x 5.501 in
---------------------------------------	--------------------------

Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	DEHP

ACCESSORIES



156EB1945A
Trippers for E1020 (Pack of 2)