

In-Wall Timer - 7-Day Standard Programmable Timer, 125 VAC, 15A, White

Item EI500WC



PRODUCT DESCRIPTION

For installation on 15 A circuits, this timer provides 24-hour or 7-day programming of lights, fans, pumps and other medium-duty loads. *NOTE: Not for use with sunlamps, saunas, or loads that could cause personal injury if timed incorrectly.

FEATURES

- ▶ 7-day programmable schedules with 14 ON/OFF events
- ▶ Automatic Daylight Saving Time (DST) adjustment
- ▶ Random mode varies ON/OFF schedule to provide a "lived-in" appearance
- ▶ Single-pole circuit
- ▶ Incandescent/fluorescent/CFL/LED compatible
- ▶ Built-in rechargeable, non-serviceable battery backup
- ▶ Requires neutral connection
- ▶ Backlit LCD display
- ▶ Decorator switch plate not included

APPLICATIONS

- ▶ Indoor Lighting Control
- ▶ Air Movement & Ventilation
- ▶ Outdoor Lighting Control

TECHNICAL DATA

General

Model Number	EI500WC
Description	7-Day Standard Programmable Timer, 125 VAC, 15A, White
UPC Code	078275105232
Brand	Intermatic
Country of Origin (Intermatic)	CHINA
Warranty Period	1-Year limited

Control Specifications

Minimum ON/OFF Times	1 min
Maximum ON/OFF Operations	14
Operation Mode	24 hour
Mechanism Type	Digital/Electrical
Backup Type	Battery
Battery Type	Rechargeable
Battery Service Type	Non-Serviceable
Application Compatibilities	Incandescent; Fluorescent; CFL; LED

Mechanical Specifications

Wall Plate Configurations	Single-Gang
---------------------------	-------------

Dimensions

Product Dimensions (H x W x D) in	4.125 x 1.75 x 1.4375 in
-----------------------------------	--------------------------

Material Specifications

Color	White
-------	-------

Load Ratings

General Purpose	15 A, 125 VAC, 60 Hz
Resistive Heater	15 A, 1875 W
Tungsten (Incandescent) Range(s)	1000 W
Electronic Ballast LED	4 A, 500 VA
Motor Load Ratings Ranges	1/4 HP, 125 VAC, 60 Hz
Inductive Load Ratings Ranges	1000 VA, 125 VAC, 60 Hz

Electrical Specifications

Input Voltage Range(s)	125 VAC, 60 Hz
Wiring Configurations	Single
Neutral Connection Required	Yes

Environmental Specifications

Temperature (operation)	32 - 104 °F / 0 - 40 °C
-------------------------	-------------------------

Packaging

Unit Carton Dimensions (H x W x D) in	4.88 x 3 x 2.13 in
---------------------------------------	--------------------

Standards and Certifications

UL Certification	cULus
California Proposition 65	DEHP