


Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper - Mechanism Only

Item R8806M101C



PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

FEATURES

- ▶ Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ▶ 14-Day skipper enables irrigation to be omitted on selected day(s)
- ▶ Allows for alternate-day scheduling
- ▶ ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ▶ Type 3R plastic indoor/outdoor enclosure

APPLICATIONS

- ▶ Agriculture Feeders
- ▶ Greenhouse Misting Control
- ▶ Landscape Water Control

TECHNICAL DATA

General	
Model Number	R8806M101C
Description	Sprinkler/Irrigation Time Switch with 14-Day Skipper - Mechanism Only
UPC Code	078275148024
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited
Control Specifications	
Minimum ON/OFF Times	12 min
Maximum ON/OFF Times	20 hours, 45 minutes
Maximum ON/OFF Operations	44
Tripper Actuating Time	12 min
Mechanism Type	Analog/Mechanical
Mechanical Specifications	
Number of Trippers Included	12
Dimensions	
Product Dimensions (H x W x D) in	10 x 6.5 x 4 in
Load Ratings	
Motor	3 HP, 240 VAC, 60 Hz
Clock Motor Voltage	240 VAC, 60 Hz
Electrical Specifications	

Switch Type	DPST
Load Voltage	240 VAC, 60 Hz
Amps Per Pole	30 A
HP	3

Packaging

Unit Carton Dimensions (H x W x L) in	4.001 x 5.501 x 8.001 in
---------------------------------------	--------------------------

Environmental Specifications

Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)
-------------------------	--------------------------------------

Standards and Certifications

CSA Certification	cCSAus
California Proposition 65	None


ACCESSORIES



156T1950A
Set of 12 Trippers for T1900, T2000, C8800, R8800 and T8800 Series



133T700A
Micro Switch for T8800 and R8800 Series



156T1954A
14 Skipper Pins for R8800, and T8800 Series

Product Image Not Available

107T73
Replacement Day Wheel Pins for T8800 and R8800 Series

Product Image Not Available

107T119
Tripper (Silver) for T8800 and R8800 Series (Day Skipper)

Product Image Not Available

133T1115A
Toggle Switch for T8800 and R8800 Series

Product Image Not Available

143T138
Relay Kit, DPST, 3 HP, 240 VAC (S)

Product Image Not Available

156T1950AD12
12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



WG730-14D
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX
125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14DMX
208-277 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series

Product Image Not Available

156T2978A
Package Accessory Trippers