

## Mechanical Time Switch - 24-Hour Mechanical Time Switch with Skip-a-Day, 480 VAC, 60Hz, 4-SPST, Outdoor Metal Enclosure, 1 Hour Interval

Item T1475BR



### PRODUCT DESCRIPTION

Similar to the T100 Series, these time switches can also handle electrical loads up to 40 A per pole. The T170 Series Time Switches allow for up to 10 ON/OFF settings per day, but give you the additional capability of skipping days in which the loads may not be needed. Each time switch will come with one set of ON/OFF trippers as well as three skipper screws to omit the schedule for at least three days.

### FEATURES

- ▶ Controls loads up to 40 A per pole
- ▶ Direct 24-hour control of most loads
- ▶ Up to 10 ON/OFF operations each day
- ▶ Minimum ON/OFF times of one hour
- ▶ Manual override
- ▶ One ON and one OFF tripper and three day-skipper screws included

### APPLICATIONS

- ▶ Timing/Scheduling ON/OFF
- ▶ Indoor Lighting Control
- ▶ Outdoor Lighting Control

### TECHNICAL DATA

General	
Model Number	T1475BR
Description	24-Hour Mechanical Time Switch with Skip-a-Day, 480 VAC, 60Hz, 4-SPST, Outdoor Metal Enclosure, 1 Hour Interval
UPC Code	078275179097
Brand	Intermatic
Country of Origin (Intermatic)	MEXICO
Warranty Period	1-Year limited

Control Specifications	
Minimum ON/OFF Times	1 hour
Maximum ON/OFF Operations	10
Skipper Wheel	Not Included
Operation Mode	24 hour
Has Manual Override	Yes
Application Compatibilities	LED; HID

Mechanical Specifications	
Enclosure Type	Outdoor type 3R metal

Dimensions	
Product Dimensions (H x W x D) in	10.125 x 6.5 x 3.625 in
Wire Size Min	#14 AWG
Wire Size Max	#8 AWG

Load Ratings	
Motor (Single-Phase)	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz
Motor (Three-Phase)	7 1/2 HP, 28 FLA @ 208 VAC, 60 Hz; 10 HP, 28 FLA @ 240 VAC, 60 Hz
Motor Single Phase Ranges	2 HP, 24 FLA @ 120 VAC, 60 Hz; 5 HP, 28 FLA @ 240 VAC, 60 Hz
Motor Three Phase Ranges	7 1/2 HP, 28 FLA @ 208 VAC, 60 Hz; 10 HP, 28 FLA @ 240 VAC, 60 Hz
Tungsten Range(s)	40 A, 120-277 VAC, 60 Hz
Electronic Ballast	16 A, 277 VAC, 60 Hz
Electronic Ballast Load Ratings Ranges	16 A, 277 VAC, 60 Hz
Inductive	40 A, 277 VAC, 60 Hz; 40 A, 240 VAC, 60 Hz; 40 A, 208 VAC, 60 Hz; 40 A, 120 VAC, 60 Hz
Resistive Load Ratings Ranges	40 A, 120-480 VAC, 60 Hz
Inductive Load Ratings Ranges	40 A, 120-277 VAC, 60 Hz
Pilot Duty Load Ratings Ranges	1000 VA, 120-277 VAC, 60 Hz

Electrical Specifications	
Wiring Option	Terminals
Input Voltage Range(s)	480 VAC, 60 Hz
Number of Circuits	1
Switch Type	4-PST
Maximum Power Consumption (W)	3 W

Packaging	
Unit Carton Dimensions (H x W x L) in	4 x 7.06 x 11.5 in

Environmental Specifications	
Temperature (operation)	-40 °F to 130 °F / (-40 °C to 54 °C)

Standards and Certifications	
UL Certification	cULus
CSA Certification	cCSAus
Other Certifications and Compatibilities	LED
UL File Number	UL916
CSA File Number	C22.2-177; LR3730
California Proposition 65	Lead

## ACCESSORIES



156T1948A  
Trippers for T170, T1400, T1800 Series  
Includes 1 ON, 1 OFF, and 1 ON with Skipper  
Extension



156T3085A  
Skipper Screws for T170 Series, T1400  
Series, and T1800 Series



124T1953  
Insulator for 4PST Time Switch



WG1573-10DMX  
208-277 VAC, 60 Hz Motor for T102, T104,  
T106, T172, T174, WH40

Product  
Image  
Not  
Available

156T1957A  
Skipper Screws (3 per package)