

### Irrigation Timer - Sprinkler/Irrigation Time Switch with 14-Day Skipper

Item T8845PV



#### PRODUCT DESCRIPTION

These irrigation timers are designed to permit one to 44 "ON" operations every 24 hours and provide watering increments down to 12 minutes or up to 20 hours and 45 minutes to ensure proper watering increments. These models also allow for biweekly scheduling with the convenient 14-day skipper for maximum water conservation and odd/even day compliance.

#### **FEATURES**

- ► Up to 44 ON/OFF settings per day
- ▶ Water metering increments from 12 minutes to 20 hours and 45 minutes
- ► 14-Day skipper enables irrigation to be omitted on selected day(s)
- Provides for every other day operation
- ON/OFF/AUTO switch enables shutdown during rainy days and extended watering during dry periods without disturbing the cycle set on dial
- ► Type 3R plastic indoor/outdoor enclosure

#### **APPLICATIONS**

- ► Agriculture Feeders
- ► Greenhouse Misting Control
- ► Landscape Water Control

#### TECHNICAL DATA

| TECHNICAL DATA                 |  |
|--------------------------------|--|
| General                        |  |
| Model Number                   | T8845PV  |
| Description                    | Sprinkler/Irrigation Time Switch with 14-Day Skipper |
| UPC Code                       | 078275700741   |
| Brand                          | Intermatic   |
| Country of Origin (Intermatic) | MEXICO   |
| Warranty Period                | 1-Year limited                                       |
|                                |  |
| Control Specifications         |  |
| Minimum ON/OFF Times           | 12 min   |
| Maximum ON/OFF Times           | 20 hours, 45 minutes                                 |

| Maximum 0N/0FF Times      | 20 hours, 45 minutes |
|---------------------------|----------------------|
| Maximum ON/OFF Operations | 44                   |
| Tripper Actuating Time    | 12 min               |
| Mechanism Type            | Analog/Mechanical    |

| Mechanical Specifications   |                                |
|-----------------------------|--------------------------------|
| Enclosure Type              | Indoor/outdoor type 3R plastic |
| Number of Trippers Included | 12                             |

| Dimensions                        |                 |
|-----------------------------------|-----------------|
| Product Dimensions (H x W x D) in | 10 x 6.5 x 4 in |

| Load Ratings        |                    |
|---------------------|--------------------|
| Motor               | 24 VAC, 60 Hz      |
| Clock Motor Voltage | 110/125 VAC, 60 Hz |



Electrical Specifications

Switch Type SPST

Load Voltage 24 VAC, 60 Hz

Amps Per Pole 20 VA

Packaging

Unit Carton Dimensions (H x W x L) in 4.25 x 7.31 x 11.75 in

**Environmental Specifications** 

Temperature (operation)  $-40 \,^{\circ}\text{F}$  to 130  $^{\circ}\text{F}$  / (-40  $^{\circ}\text{C}$  to 54  $^{\circ}\text{C}$ )

Standards and Certifications

CSA Certification cCSAus
California Proposition 65 Lead



#### **ACCESSORIES**



156T1950A

Set of 12 Trippers for T1900, T2000, C8800, Micro Switch for T8800 and R8800 Series R8800 and T8800 Series



133T700A



156T1954A

14 Skipper Pins for R8800, and T8800 Series Mechanical Water Heater Time Switch



T104-20

## **Product I**mage **Available**

Replacement Day Wheel Pins for T8800 and R8800 Series

# **Product I**mage **Available**

Tripper (Silver) for T8800 and R8800 Series (Day Skipper)



119T86A

24 VAC 20 VA Transformer, with #10 Ring Terminals

## **Product I**mage **Available**

124T2097

Insulator for R8806P101C, T8805P101C, T8845PV

# **Product X**mage **Available**

133T1115A

Toggle Switch for T8800 and R8800 Series

# **Product X**mage **Available**

156T1950AD12

12 Bags of 156T1950A Trippers for T1900, T2000, C8800, R8800, and T8800 Series



WG730-14D

125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG730-14DMX

125 VAC, 60 Hz Motor for R8800, T1900, T1970, and T8800 Series



WG733-14D

T1970, and T8800 Series



WG733-14DMX

T1970, and T8800 Series

**Product I**mage **Available** 

156T2978A

208-277 VAC, 60 Hz Motor for R8800, T1900, 208-277 VAC, 60 Hz Motor for R8800, T1900, Package Accessory Trippers