

# KLV217

12 VOLT, DIE-CAST ALUMINUM, MICRO-FLOOD® LED

## FEATURES

- Unique swivel mount provides superior aiming without loosening over time
- Available in 3500K and 5100K standard CCT



## Certifications



## SPECIFICATIONS



Approx. Weight = 3.16 lbs.



## ORDERING CODE

KLV217			
<b>Fixture<sup>1</sup></b>	<b>Electrical Module</b>		<b>Fixture Finish</b>
	Source	Color Temperature	Aluminum
	3L 3 LEDs	3K 3500K 5K 5100K	BL Black DB Dark Bronze GR Verde Green

<b>Fixture Options</b>	<b>Transformer Options</b>	<b>Mounting Options</b>
Barn Doors	Refer to 112V Above-Grade/In-Grade Transformers spec sheet	Refer to 120 Volt Mounting Options Spec Sheet for individual mounting options.
BD215BL Black		
BD215DB Dark Bronze		
BD215GR Verde Green		
Fixed Hood		
FH215BL Black		
FH215DB Dark Bronze		
FH215GR Verde Green		

<sup>1</sup> U.S. PATENT D298,656

# KLV217

12 VOLT, DIE-CAST ALUMINUM, MICRO-FLOOD® LED

## SPECIFICATIONS

### Housing and Lens Frame:

- Die-cast low copper alloy (<0.6% Cu) aluminum.

### Swivel:

- Die-cast aluminum with locking teeth and 1/2" solid brass NPT mount. Provides horizontal rotation independent of the threaded mount. Swivel locked by 1/4-20 stainless set screw. Clear anodized prior to powder coating for added corrosion resistance.

### Gasketing:

- Silicone gaskets throughout.

### Fasteners:

- Stainless steel.

### Wiring:

- 6' No. 18-2 12 Volt cable with fork connectors.

### Optical System:

- A total of 3 LED emitters configured in a rectangular array comprised together as a module. Available in 3500K and 5100K.

### Driver:

- Constant current 3.8W electronic driver. Available in 12V input. -40°F. starting temperature. All drivers are Underwriters Laboratories recognized.

### Finish:

- Each luminaire receives a fade and abrasion resistant, electrostatically applied, thermally cured, triglycidal isocyanurate (TGIC) polyester powdercoat finish. Standard colors include (BL) Black, (DB) Dark Bronze, (GR) Verde Green.

### Certifications and Listings:


- UL Listed to U.S. and Canadian safety standards for wet locations.

## OPTIONS

### Barn Doors

#### BD215

Extruded aluminum, fully adjustable. Provides beam and glare control. Available in Black, Dark Bronze or Verde Green finish.



### Fixed Hood

#### FH215

Formed .062" thick aluminum. Provides glare control. Available in Black, Dark Bronze or Verde Green finish.

