

Lightcraft Outdoor's Premium LED MR16 lamps are available in a variety of wattages, Kelvin color options and beam angles. Optimized for outdoor use.











PROJECT	DATE
ТҮРЕ	CATALOG #

# LED MR16 LAMPS PREMIUM SERIES

#### **KEY FEATURES**

- •DESIGNED FOR OUTDOOR USE IN ENCLOSED FIXTURES
- •FULLY POTTED PC BOARD
- OPTIMIZED ESD (ELECTRO-STATIC DISCHARGE)
- ·DIMMABLE+
- **•UV PROTECTED OPTIC LENS**
- ·ETL LISTED, CE AND FCC COMPLIANT
- •3 YEAR LIMITED WARRANTY

#### PRODUCT SPECIFICATIONS

DIMENSIONS 1-5/8"L X 1-7/8"W

(3.5W-4.5W)

DIMENSIONS 1-3/4"L X 2"W

(5.5W-7W)

BASE MR16 (G4 BASE)


CHIPSET EPISTAR

VOLTAGE 12-24V AC/DC

DIMMABLE YES+

#### STEP 1

### LED LAMP CONFIGURATION



15D 15° NARROW\*

45D 45° STANDARD

60D 60° WIDE

+PRIMARY SIDE DIMMING: Requires LED magnetic low voltage (MLV) dimmable transformer and compatible LED dimmer (MLV) - Primary Side or Lightcraft 12V in-line dimmer.

For more information see installation guidelines.

Fully tested with Lutron Diva (DVLV-600P) dimmer and Lightcraft dimmable transformers and LED lamps.

+LOW VOLTAGE SIDE DIMMING: Requires Lightcraft 12V In Line Dimmer

## **KELVIN COLOR OPTIONS**



# **BEAM ANGLE OPTIONS**







Medium beam angle ideal for small to medium size trees, walls and columns



Wide beam angle ideal for wider trees, foliage and walls

- \* 15° Only available in 3.5w and 5.5w 2700k or 3000k
- + Lumens calculated at 3000K (-5% for 2700K)