



Shown actual size: Caséta Wireless in-wall dimmer and 1-gang Claro wallplate in White (WH).

Product family features

- Control your lights from anywhere
- Uses Lutron Clear Connect radio frequency (RF) technology, which provides reliable RF communication with Pico wireless remotes, Radio Powr Savr wireless occupancy/vacancy sensors, and Smart Hubs
- LED+ models available
- Control and schedule lights from the Lutron App when paired with a Smart Hub
- Use Pico wireless remotes for additional dimmers/switches in multi-location applications
- Communicates at 434 MHz frequency
- Coordinating Claro wallplates only available separately
- All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

Direct load type compatibility

- Dimmable LED/CFL lighting (screw-base)
- Incandescent/halogen lighting
- Magnetic low-voltage lighting
- Electronic low-voltage lighting
- LED lighting
- Fluorescent lighting
- Switched lighting/fan/motor

Load type requiring load interface

- Neon/cold cathode lighting

Lighting load interfaces may be required for some load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

Control types

- Single-pole (1 location)
- 3-way (2 locations)
- Wireless multi-location (up to 11 locations)

Available finishes

Use **BOLD** color code in model number (Example: PD-6WCL-**WH**)

Gloss



WH
White



LA
Light Almond



IV
Ivory



BL
Black

Metal wallplate*



SS
Stainless Steel

* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control.

Switch & Remote Kit



- Eliminates fumbling around in the dark
 - Add a switch anywhere
 - Add a Smart Hub anytime
- Ideal for garages, hallways, and kitchens*

Switch & Remote Kit

Smart Switch, Wallplate, Remote, Bracket P-PKG1WS-WH

Smart Switch Starter Kit



- Always come back to a well-lit home
 - Using the Lutron App, easily check which lights are on or off
 - Automatically schedule lights to turn on and off anytime
- Ideal for outdoor lighting*

Smart Switch Starter Kit

Switch, Wallplate, Smart Hub P-BDG-PKG1WS

3-Way Dimmer Kit with Remote



- Eliminates fumbling around in the dark
 - Add a switch anywhere
 - Add a Smart Hub anytime
- Ideal for garages, hallways, and kitchens*

3-Way Dimmer Kit with Remote

Smart Dimmer, Wallplate, Wallplate P-DIM-3WAY-WH

Dimmer Kit with Smart Hub



- Create the right light for any occasion
 - Using the Lutron App, easily check which lights are on or off
- Ideal for the kitchen and living, family, and dining rooms*

Dimmer Kit with Smart Hub

Dimmer, Remote, Smart Hub P-BDG-PKG1W

Lamp Dimmer & Remote Kit



- Adjust lights on either side of the bed
 - Control multiple lamps in a room with one remote
- Ideal for bedrooms, living rooms, studies, and home offices*

Lamp Dimmer & Remote Kit

Lamp Dimmer, Remote P-PKG1P-WH

Visit lutron.com/CasetaKits for more information

Smart Lamp Timer Kit



- Perfect for rooms with no overhead lighting
 - Control lights with voice integration, the Lutron App, or a Pico remote
- Ideal for living rooms and bedrooms*

Smart Lamp Timer Kit

Lamp Dimmer, Remote, Smart Hub P-BDG-PKG1P

Wireless in-wall dimmers



- Simple, intuitive design with on, off, and raise/lower buttons
- Provides true dimming from each location with Pico wireless remotes
- Offers superior dimming of dimmable LEDs/CFLs, as well as halogens and incandescents
- PRO and ELV+ models work with magnetic low-voltage lighting, and are compatible with Lutron 2-wire forward phase LED drivers, Tu-Wire fluorescent ballasts and load interfaces; ELV+ models also work with electronic low-voltage lighting

Dimmable LED/CFL (screw-base) dimmer

Incandescent/halogen dimmer

Wireless in-wall LED+ dimmer

Multi-location[†]/single-pole PD-6WCL-**XX**¹
120 V 150 W (LED/CFL),
600 W (Inc)

Visit lutron.com/LEDfinder for our online compatibility tool.

Adjustable low-end trim.

Dimmable LED (screw-base) dimmer

Incandescent/halogen dimmer

Magnetic low-voltage dimmer

Electronic low-voltage dimmer

Hi-lume 1% 2-wire LED driver dimmer

Tu-Wire fluorescent ballast dimmer

Wireless in-wall ELV+ dimmer^{**}

Multi-location[†]/single-pole PD-5NE-**XX**¹
120 V 250 W (LED), 500 W (Inc),
400 VA/300 W (MLV),
500 W (ELV),
400 W (Hi-lume 1% LED driver, max. 20),
3.3 A (Tu-Wire fluorescent ballast)

Visit lutron.com/LEDfinder for our online compatibility tool.

Adjustable low-end trim.

Dimmable LED (screw-base) dimmer

Incandescent/halogen dimmer

Magnetic low-voltage dimmer

Hi-lume 1% 2-wire LED driver dimmer

Tu-Wire fluorescent ballast dimmer

Wireless in-wall dimmer PRO^{††}

Multi-location[†]/3-way*/ PD-10NXD-**XX**¹
single-pole
120 V 250 W (LED), 1000 W (Inc),
1000 VA/800 W (MLV),
520 W (Hi-lume 1% LED driver, max. 13),
5 A (Tu-Wire fluorescent ballast)

Visit lutron.com/compatibility for our online compatibility tool.

Adjustable low-end trim.

XX¹: Gloss color codes

Wallplates not included. Order separately.

* Works with standard mechanical 3-way switch

** Neutral wire connection required

† For multi-location applications, replace additional switches with Pico wireless remotes

†† **Neutral wire connection available, not required** (required for LED drivers, fluorescent ballasts, and interfaces)

Wireless in-wall electronic switches



- Offers large on and off buttons
- 2-wire switch ideal for retrofit applications
- Neutral wire switch ideal for higher wattages and lower minimum loads

Switches

Wireless in-wall electronic switch**

Multi-location†/3-way*/	PD-6ANS- XX ¹
single-pole	
120V 6A light, 3.6A (1/4HP) fan	

Wireless in-wall electronic switch PRO

Multi-location†/3-way*/	PD-5WS-DV- XX ¹
single-pole	
120/277V 5A light, 3A fan	

Fan controls



- Provides true control from each location with the Pico fan wireless remote
- Save fan speed preference with the “favorite” button
- 4 quiet fan speeds

Fan controls

Fan controls—quiet 4-speed

Multi-location/single-pole	PD-FSQN- XX ¹
120V 1.5A	

Wireless plug-in lamp dimmer



- Features two receptacles for simultaneous control of two lamps
- Simply plugs into a standard wall receptacle for easy installation
- Can be converted to a switch for control of other lighting loads

Dimmable LED/CFL (screw-base) lamp dimmer

Incandescent/halogen lamp dimmer

Wireless plug-in LED+ lamp dimmer

Single-pole	PD-3PCL-WH
120V 100W (LED/CFL), 300W (Inc)	

Visit lutron.com/LEDfinder for our online compatibility tool.

XX¹: Gloss color codes
Wallplates not included. Order separately.

- * Works with standard mechanical 3-way switch
- ** Neutral wire connection required
- † For multi-location applications, replace additional switches with Pico wireless remotes

Outdoor Smart Plug



- Able to withstand all weather conditions
- IP66 certified
- Indicator LED light with status and error reporting available

Switching Module

Outdoor Smart Plug PD-15OUT-BL
120V 15A light, 1/2HP motor/pump

Motion sensor



- 10-year typical battery life
- 180 degree field of view
- Uses XCT technology for fine motion detection
- Occupancy/Vacancy models available



Motion sensor

Occupancy/Vacancy PD-OSENS-WH
Vacancy only PD-VSENS-WH

Pico wireless remote



- Only select models shown below, see Pico section for full family including Caséta PRO models

Pico wireless remotes

2-button PJ2-2B-**XX**¹-L01
2-button raise/lower PJ2-2BRL-**XX**¹-L01
3-button raise/lower PJ2-3BRL-**XX**³-L01R
3-button raise/lower w/wallplate
and wallbox adapter PJ2-WALL-WH-L01
Wallbox adapter PICO-WBX-ADAPT

Tabletop pedestals

Single pedestal L-PED1-**XX**²
Dual pedestal L-PED2-**XX**²
Trip pedestal L-PED3-**XX**²
Quad pedestal L-PED4-**XX**²

Car visor clip

Clip PICO-CAR-CLIP

XX¹: Available in Gloss colors
XX²: Available in Gloss White (WH) and Black (BL)
XX³: Available in Gloss White (WH) and Light Almond (LA)