
Wallplates for Caséta Wireless, Diva, Luméa, Maestro, Maestro Wireless, Pico wireless, Skylark, Skylark Contour, Sunnata, Vive Maestro Wireless controls, and Vive accessories



1-gang*,**	CW-1- XX 1
W: 2.94 in (75 mm)	SC-1- XX ²
2-gang*,**	CW-2- XX 1
W: 4.75 in (121 mm)	SC-2- XX ²
3-gang*,**	CW-3- XX 1
W: 6.56in (167 mm)	SC-3- XX ²
4-gang*,**	CW-4- XX 1
W: 8.37 in (213 mm)	SC-4- XX ²
5-gang*	CW-5- XX 1
W: 10.18in (259mm)	SC-5- XX ²
6-gang*	CW-6- XX 1
W: 12in (305mm)	SC-6- XX ²

Important note

Multiple devices with line and low-voltage can be mounted behind a common wallplate using a standard barrier backbox. For more information consult Lutron Application Note #213, Combining Low-Voltage and Line Voltage Wiring Devices in a Multi-Gang Box, at lutron.com/applicationnotes.

XX¹: Gloss and metal color codes

XX²: Satin colors codes **XX**³: Gloss color codes

XX4: Available in Snow (SW), Biscuit (BI), Midnight (MN), Taupe (TP), Mist (MI), and Signal Red (SR)



Custom engraving available for all Designer, Traditional, New Architectural, and Architectural style wallplates (except Stainless Steel). For wallplate engraving schedules, go to **lutron.com/engraving**.

Cable jacks



- F-style, 75-Ohm coaxial cable
- Wallplate sold separately

Single cable jack CA-CJ-**XX**³ SC-CJ-**XX**⁴

Telephone jacks



- 6-conductor telephone jack, RJ11
- Wallplate sold separately

Single telephone jack

CA-PJ-XX³

SC-PJ-XX4

6-port frame



- · Shipped with six blanks in matching colors
- Connectors sold separately
- · Connectors snap in (no tools required)
- Connectors available in White (WH), unless noted

Field customizable 6-port frame

6-port frame	CA-6PF- XX 1
	SC-6PF- XX ⁴

Connectors for 6-port frame



Telephone/network jacks

8-conductor,	CON-1P-C5E- XX ³
RJ45 category 5e	
8-conductor,	CON-1P-C6- XX 3
RJ45 category 6	





MT-RJ feed through	CON-1F-MTRJ-WH
SC simplex	CON-1F-SC-WH
LC non-flush mount	CON-1F-LC-WH
ST-style	CON-1F-ST-WH



Cable jack

F-style,	CON-1C- XX ³
75-Ohm coaxial cable	



BNC jack

BNC connector, 50-Ohm	CON-1B-WH
Connectors only for use with (6-port frame.

Receptacles



 Tamper-resistant receptacles include tamper-resistant shutter mechanism (shutters are white)

Receptacles

15A	125 V	CAR-15- XX 1
		SCR-15- XX 2
20 A	125 V	SCR-20- <u>XX</u> 2

Tamper-resistant receptacles

15A 125V	CARS-15-TR- XX 1
	SCRS-15-TR-XX ²
20A 125V	SCRS-20-TR-XX2

USB receptacles



- · Includes two USB ports
- · Ports are rated for a minimum of 10,000 insertions and removals

Tamper-resistant USB receptacles

15A 125V	CAR-15-UBTR-XX1
	SCR-15-UBTR-XX ²

XX1: Gloss color codes

XX²: Satin color codes

XX3: Available in White (WH) and Black (BL) XX4: Available in Snow (SW), Biscuit (BI), Midnight (MN), Taupe (TP), Mist (MI),

and Signal Red (SR)

Wallplates not included. Order separately.