

Available finishes

Use **BOLD** color code in model number (Example: DVCL-153P-**BL**)

Gloss



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Satin Finishes



BW
Brilliant White



GL
Glacier White



SW
Snow



RW
Architectural
White



LG
Lunar Gray



MI
Mist



PB
Pebble



CS
Cobblestone



SL
Slate



MN
Midnight



BI
Biscuit



SD
Sand



TP
Taupe



PM
Pumice

Metal wallplate*



CY
Clay



SA
Sage



EP
Espresso



TF
Truffle



DE
Deep Sea



SR
Signal Red



SS
Stainless Steel

* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) or Midnight (MN) controls.

Dimmers



- Paddle turns on/off
- Slide up to brighten, down to dim
- LED+ dimmers provide reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents

Dimmable LED/CFL (screw-base) dimmers

Incandescent/halogen dimmers

LED+ dimmers

3-way/single-pole	DVCL-153P- XX ¹
120V 150W (LED/CFL), 600W (Inc)	DVSCCL-153P- XX ²

3-way/single-pole	DVCL-253P- XX ¹
120V 250W (LED/CFL), 600W (Inc)	DVSCCL-253P- XX ²
350W (Hi-lume 1% LED driver, max. 8)	

Visit lutron.com/LEDfinder for our online compatibility tool.

Adjustable low-end trim.

Dimmable LED/CFL (screw-base) dimmers

Incandescent/halogen dimmers

Electronic low-voltage dimmers

Reverse-phase dimmers*

3-way/single-pole	DVRP-253P- XX ¹
120V 250W (LED/CFL), 500W (Inc), 500W (ELV)	DVSCR-253P- XX ²

When dimming LEDs/CFLs, only bulbs marked or rated as dimmable with reverse-phase may be used.

Visit lutron.com/LEDfinder for our online compatibility tool.

No low-end trim.

XX¹: Gloss color codes

XX²: Satin color codes

Wallplates not included. Order separately.

Incandescent/halogen dimmers

Dimmers

Single-pole	DV-10P- XX ¹
120V 1000W	DVSC-10P- XX ²
3-way/ 120V 1000W	DV-103P- XX ¹
	DVSC-103P- XX ²

Magnetic low-voltage dimmers

Dimmers

Single-pole	DVLV-600P- XX ¹
120V 600VA (450W)	DVSCLV-600P- XX ²
Single-pole	DVLV-10P- XX ¹
120V 1000VA (800W)	DVSCLV-10P- XX ²
3-way	DVLV-603P- XX ¹
120V 600VA (450W)	DVSCLV-603P- XX ²
3-way	DVLV-103P- XX ¹
120V 1000VA (800W)	DVSCLV-103P- XX ²

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

Electronic low-voltage dimmers

Dimmers*

Single-pole	DVELV-300P- XX ¹
120V 300W	DVSCELV-300P- XX ²
3-way	DVELV-303P- XX ¹
120V 300W	DVSCELV-303P- XX ²

* Requires neutral wire connection

3-wire LED driver/fluorescent ballast dimmers

Dimmers*

3-way/single-pole 120V 8A	DVF-103P- XX ¹ DVSCF-103P- XX ²
3-way/single-pole 277V 6A	DVF-103P-277- XX ¹ DVSCF-103P-277 XX ²

No derating required if ganged.

Adjustable low-end trim.

0-10V LED/fluorescent fixture dimmers (current sink control)

Dimmers

3-way/single-pole 120–277V 8A	DVSTV- XX ¹ DVSCSTV- XX ²
----------------------------------	--

50mA max control current

No power pack required.

No derating required if ganged.

0-10V LED/fluorescent fixture dimmers (current sink control – power pack required)

Dimmers*

Single-pole 30mA max control current	DVTV- XX ¹ DVSCTV- XX ²
---	--

Control provides dimming signal only. For dimming with on/off switching, **use with Lutron power pack:** PP-DV or PP-347H.

Compatible with any IEC 60929 Annex E compliant driver or ballast.

No derating required if ganged.

Tu-Wire fluorescent ballast dimmers

Dimmers

3-way/single-pole 120V 5A	DVFTU-5A3P- XX ¹ DVSCFTU-5A3P- XX ²
------------------------------	--

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

XX¹: Gloss color codes
XX²: Satin color codes
Wallplates not included. Order separately.

* **Requires neutral wire connection**