





Shown actual size: Skylark dimmer and 1-gang Claro wallplate in White (WH).









Product family features

- Rocker switch returns light to light level indicated by slider on preset dimmers
- Slide up to brighten, down to dim
- LED+ models available
- Coordinating Claro and Stainless Steel wallplates only available separately
- All models must be derated unless otherwise noted. Visit lutron.com/multigang for more information.

Control types

-  Single-pole (1 location)
-  3-way or 4-way (2 or more locations)

Direct load type compatibility

-  Dimmable LED/CFL lighting (screw-base)
-  Incandescent/halogen lighting
-  Magnetic low-voltage lighting
-  Electronic low-voltage lighting
-  LED lighting
-  Fluorescent lighting
-  Ceiling fans
-  Ceiling fan/lights

Load type requiring load interface

-  Neon/cold cathode lighting

Lighting load interfaces may be applicable for some additional load type, voltage, and capacity combinations. For additional information see "Lighting Load Interfaces."

Available finishes

Use **BOLD** color code in model number (Example: SCL-153P-**GR**)

Gloss



WH
White



LA
Light Almond



AL
Almond



IV
Ivory



GR
Gray



BR
Brown



BL
Black

Metal wallplates*



SS
Stainless Steel

* Stainless Steel metal wallplate only available separately and includes black plastic trim/adaptor, visible from side. Match with separate Black (BL) control.

Dimmers



- Preset models include rocker switch to return to light level indicated by slider
- Slide up to turn on/brighten, down to turn off/dim
- LED+ dimmer provides reliable dimming of dimmable LEDs/CFLs, as well as halogens and incandescents



Incandescent/halogen dimmers

Dimmers with on/off switch

| | |
|---------------------------|--------------------------------|
| Single-pole 120V 1000W | S-10P- XX ¹ |
| 3-way 120V 1000W | S-103P- XX ¹ |

Slide-to-off dimmers

| | |
|---------------------------|--------------------------------|
| Single-pole 120V 1000W | S-1000- XX ¹ |
|---------------------------|--------------------------------|

Dimmers with on/off switch and locator light

| | |
|---------------------------|----------------------------------|
| Single-pole 120V 1000W | S-10PNL- XX ¹ |
| 3-way 120V 1000W | S-103PNL- XX ¹ |

Dimmable LED/CFL (screw-base) dimmer

Incandescent/halogen dimmer

LED+ dimmer with on/off switch

| | |
|---|----------------------------------|
| 3-way/single-pole 120V 150W (LED/CFL), 600W (Inc) | SCL-153P- XX ¹ |
|---|----------------------------------|

Visit lutron.com/LEDfinder for our online compatibility tool.

Adjustable low-end trim.

XX¹: Gloss color codes

Magnetic low-voltage dimmers

Dimmers with on/off switch

| | |
|-----------------------------------|----------------------------------|
| Single-pole 120V 600 VA (450W) | SLV-600P- XX ¹ |
| 3-way 120V 600 VA (450W) | SLV-603P- XX ¹ |

The stated VA (volt-ampere) rating includes the magnetic transformer heat losses and the lamp load. The stated W (watt) rating is the maximum lamp wattage based on assumed 20% transformer loss.

Electronic low-voltage dimmers

Dimmers with on/off switch*

| | |
|--------------------------|-----------------------------------|
| Single-pole 120V 300W | SELV-300P- XX ¹ |
| 3-way 120V 300W | SELV-303P- XX ¹ |

3-wire LED driver/fluorescent ballast dimmers

Dimmers with on/off switch*

| | |
|------------------------|--------------------------------------|
| Single-pole 120V 8A | SF-10P- XX ¹ |
| Single-pole 277V 6A | SF-12P-277- XX ¹ |
| 3-way 120V 8A | SF-103P- XX ¹ |
| 3-way 277V 6A | SF-12P-277-3- XX ¹ |

No derating required if ganged.
Adjustable low-end trim.

Tu-Wire fluorescent ballast dimmer

Dimmer with on/off switch

| | |
|------------------------------|-----------------------------------|
| 3-way/single-pole 120V 5A | SFTU-5A3P- XX ¹ |
|------------------------------|-----------------------------------|

Compatible with Advance Mark X and Sylvania POWERSENSE fluorescent ballasts, in addition to Lutron Tu-Wire.

XX¹: Gloss color codes
Wallplates not included. Order separately.

* Requires neutral wire connection

Dual slide-to-off dimmer

(two loads)



Dimmers (left/right)

- Slide up to turn on/brighten, down to turn off/dim

Slide-to-off fan controls



- Slide up to turn on/increase speed, down to turn off decrease speed
- 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)
- Fully variable model also available (for use with multiple ceiling paddle or exhaust fans)

Incandescent/halogen dimmer

Dual slide-to-off dimmer

| | |
|-------------------------|------------------------------|
| Single-pole | S2-L- XX ¹ |
| 120V 300W dimmer (left) | |
| Incandescent/halogen | |
| 300W dimmer (right) | |
| Incandescent/halogen | |

Fan controls

Slide-to-off fan controls—quiet 3-speed

| | |
|-------------|-----------------------------------|
| Single-pole | SFSQ-F- XX ¹ |
| 120V 1.5A | |
| Single-pole | SFSQ-F-HO- XX ¹ |
| 120V 2A | |

SFSQ-F-HO model for use with Hunter Original Series fans.

No derating required if ganged.

Slide-to-off fan control—fully variable

| | |
|-------------|--------------------------------|
| Single-pole | SFS-5E- XX ¹ |
| 120V 5A | |

Control provides an additional wire for fan light switching (360W, incandescent/halogen). Light turns on when fan is on, and off when fan is off.

Fully variable fan controls are commonly known as solid state fan controls.

XX¹: Gloss color codes

Wallplates not included. Order separately.

Slide-to-off fan/light control with on/off light switch

(two loads)



Fan control (top)

- Slide up to turn on/increase speed, down to turn off/decrease speed
- 3 quiet fan speeds designed to prevent motor hum (for use with only one ceiling paddle fan)

Switch (bottom)

- Rocker switch turns light on/off

✂ Fan control/light control

Slide-to-off fan/light control—quiet 3-speed with on/off light switch (two loads)

Single-pole SFSQ-LF-**XX**¹

120V 1.5A fan (top)

360W switch (bottom)

Incandescent/halogen

No derating required if ganged.

Dual slide-to-off fan/light control

(two loads)



Fan control (left)

- Slide up to turn on/increase speed, down to turn off/decrease speed

Dimmer (right)

- Slide up to turn on/brighten, down to turn off/dim

✂ Fan/light controls

Dual slide-to-off fan/light control—quiet 3-speed

Single-pole

S2-LFSQ-**XX**¹

120V 1.5A fan (left)

300W dimmer (right)

Incandescent/halogen

No derating required if ganged.

Dual slide-to-off fan/light control—fully variable

Single-pole

S2-LF-**XX**¹

120V 2.5A fan (left)

300W dimmer (right)

Incandescent/halogen

Fully variable fan controls are commonly known as solid state fan controls.

○ Replacement knobs

Standard knob

SK-**XX**²

Split knobs

Contact Customer Service

XX¹: Gloss color codes

XX²: Available in Gloss White, Ivory, Almond, and Light Almond