

Standard Models

W	HITE				
MFG CATALOG NUMBER	MFG MODEL NUMBER	SELECTABLE INSTALLATION WATTAGE	MAX BTUs	VOLTS	MAX AMPS
09488202	E3035DWBW	750 or 1500	5120	120	13
09488302	E3038DWBW	900 or 1800	6143	120	15
09488802	H3032DWBW	750 or 1000 - 1500 or 2000	6826	208 / 240	8
09489002	G3032DWBW	2000	6826	277	7

Field Installed Accessories

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION			
09968402	30R	24 VOLT RELAY			
09968502	30R2	120 VOLT RELAY			
09515002	30R8	208/240 VOLT RELAY			
09514902	30R7	277 VOLT RELAY			
09969702	303EX8RW	1" EXTENDER			
09969602	303EX16RW	2" EXTENDER			
09969502	303EX32RW	4" SURFACE MOUNT FRAME			
04600302	TB3000	T-BAR FRAME			
DISCONNECT INCLUDED					

▲ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov



Wattage selectable at time of installation - models shipped wired to highest wattage

- Fan purge circuit (has 2 wire control circuit for use with remote wall thermostat)
- Models may not be used with remote double pole thermostat
- · Drywall depth embossments on back can
- Powder coated 18 gauge steel front
- · Manual reset thermal limit
- Steel block fin elementPropeller style fan blade 1060 RPM / 100 CFM
- · Weight 6 lbs.
- Optional field installed control voltage relays available
- Rough in dimensions 9 1/4" Wide 12 1/8" High 3 5/8" deep
- Grill dimensions: 9 25/32" Wide 13" High
- · Made in U.S.A.

3380 Series Commercial Fan Forced Ceiling Heater





▲ WARNING: This product can expose you to chemicals including nickel which is known to the State of California to cause cancer, and chromium, which is known to the State of California to cause birth defects and/or reproductive harm. For more information go to www.P65Warnings.ca.gov.

Product Specifications

The heaters are to be constructed of a heavy gauge steel housing. The finish shall be baked-on powder coat in Ceiling White color. The units shall be available in ratings from 1500 through 4800 Watts with an optional factory installed single pole thermostat.

The heaters have a low speed 600-RPM motor, which drives a vane axial blower to deliver a quite 175 CFM's of down flow air. The heating element shall be of the block finned type with large, parallel steel fins for quick heat transfer. Unit shall have as standard, a manual reset capillary type limit control, for added safety. Unit weight 22 pounds.

Features & Standard Models

Recess, Surface, or "T" Bar Mounting

- Fan purge circuit (has 2 wire control circuit for use with remote wall thermostat)
- · Disconnect switch
- White powder coated 18 gauge steel grill
- Manual reset thermal limit
- · Steel block fin element
- Vane axial fan blade:
 - 1.5KW 4.0KW units: 700 RPM motor; 175 CFM 4.8KW units: 900 RPM motor; 200 CFM
- Rough in dimensions:
- $14 \frac{1}{8}$ " wide x 19 ½" high x 4" deep
- · Grill dimensions:
- $16\frac{3}{16}$ " wide x 21" high
- Optional factory installed tamper resistant thermostat
- · Made in U.S.A.

MFG CATALOG NUMBER	MFG MODEL NUMBER	KW	BTUs	VOLTS	PH	AMPS	TEMP RISE	
03664802	E3383D-RP	1.5	5120	120		12.5	27 °F	
03662902	F3386D-RP	4.0	13600	208	1	19.2	72 °F	
03663002	F3387D-RP	4.8	16382	208		23.1	76 °F	
03663402	HF3384D-RP	2.0 / 1.5	6826/5120	240/208		8.3/7.2	36 °F	
03663502	HF3385D-RP	3.0 / 2.3	10200/7679	240/208		12.5/10.8	54 °F	
03663602	HF3386D-RP	4.0 / 3.0	13600/10200	240/208		16.8/14.4	72 °F	
03663702	H3387D-RP	4.8	16382	240		20	76 °F	
03665002	G3383D-RP	1.5	5120	277		5.4	27 °F	
03664102	G3384D-RP	2.0	6826	277		7.2	36 °F	
03664202	G3385D-RP	3.0	10200	277		10.8	54 °F	
03664302	G3386D-RP	4.0	13600	277		14.4	72 °F	
03664402	G3387D-RP	4.8	16382	277		17.3	76 °F	
	International Models							
04708802	M3384D-RPi	1680	5734			7.6	30 °F	
04708902	M3385D-RPi	2520	8600	220	1	11.5	50 °F	
04709002	M3386D-RPi	4032	13761			18.3	72 °F	

Accessories

MFG CATALOG NUMBER	MFG MODEL NUMBER	DESCRIPTION	WT. (LBS)
03778502	BOX3310	Additional Back Can	10
03811002	3380EX33	Surface Mounting Adapter	5
04600202	TB3380	2X2 T-Bar Mounting Kit	7
Thermostat- Add suffix T to model Factory installed single pole. Range-40° F-110° F			