

# ONC Standard Convector



## Features

### Color

- Standard: white.
- Optional (upcharge applicable): almond, metallic silver, bronze, aluminum, semi-gloss black, metallic charcoal, sand.
- Custom colors available upon request.

### Finish

- Standard: epoxy/polyester powder paint.

### Voltage

- 120V, 208V, 240/208V, 277V, 347V, 480V, 600V, 60 Hz, 1-phase.

### Construction

- 20-gauge steel.
- Warm air outlet that directs the air to the center of the room.
- Bar grilles prevent insertion of foreign objects.
- High-limit temperature control with automatic reset.

### Heating element

- 2 stainless steel tubular heating elements with aluminum fins.
- Floating heating element on high-temperature nylon bushings reducing expansion noises.

### Watt density

- 700W/ft. (2320W/m).

### Control

- Built-in non programmable electronic thermostat for the 120V to 240V models (-TH models).
- Wall thermostat (not included).

### Installation

- 4 in. (102 mm) minimum clearance to floor and from an adjacent wall.
- Quick surface-mounted installation, with the included wall mounting bracket.

### Warranty

- 5-year warranty against defects.

*Ouellet highly recommends the use of an electronic wall thermostat for greater comfort.*

### Application

- Kitchen, living room, family room, bedroom, basement.

# ONC

## Models

Volts	Watts	Product #		Length		Weight	
		Without thermostat	Built-in thermostat	in.	mm	lb	kg
120	500	ONCU0502BL	ONCU0502BL-TH	18	457	13	6
120	1000	ONCU1002BL	ONCU1002BL-TH	23 9/16	598	16.7	7.6
120	1500	ONCU1502BL	ONCU1502BL-TH	29 1/16	739	20	9.12
208	500	ONCU0508BL	ONCU0508BL-TH	18	457	13	6
208	1000	ONCU1008BL	ONCU1008BL-TH	23 9/16	598	16.7	7.6
208	1500	ONCU1508BL	ONCU1508BL-TH	29 1/16	739	20	9.12
208	2000	ONCU2008BL	ONCU2008BL-TH	34 5/8	880	24	10.9
240/208	500/375	ONCU0500BL	ONCU0500BL-TH	18	457	13	6
240/208	1000/750	ONCU1000BL	ONCU1000BL-TH	23 9/16	598	16.7	7.6
240/208	1500/1125	ONCU1500BL	ONCU1500BL-TH	29 1/16	739	20	9.12
240/208	2000/1875	ONCU2000BL	ONCU2000BL-TH	34 5/8	880	24	10.9
277	500	ONCU0577BL	-	18	457	13	6
277	1000	ONCU1077BL	-	23 9/16	598	16.7	7.6
277	1500	ONCU1577BL	-	29 1/16	739	20	9.12
277	2000	ONCU2077BL	-	34 5/8	880	24	10.9
480	1000	ONCU1004BL	-	23 9/16	598	16.7	7.6
480	1500	ONCU1504BL	-	29 1/16	739	20	9.12
480	2000	ONCU2004BL	-	34 5/8	880	24	10.9

## Options

Product # Kit	Product # Factory installed*	Description
KIT-ONCU-TRIAC-347	TRIAC	Single-pole electronic relay, coil 24V, without transformer, 15A at 347V max.
KIT-ONCU-TRIAC-347T	TRIACT	Single-pole electronic relay, coil 24V, with transformer, 15A at 208V, 240V, 277V, 347V
KIT-ONCU-TRIAC-600	TRIAC	Single-pole electronic relay, coil 24V, without transformer, 6A at 600V max.

\* For factory installed options, add the option number to the product number. See the **Product Code** section inside the front cover.  
 Standard color is white.  
 Upcharge applicable for optional colors shown in the color chart section.  
 Other voltages available upon request.

