

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed

Technical Specifications		
Performance <hr/> Product Type: Small-Reflector Input Wattage: 4.5W Lumens (Nominal): 350lm Efficacy: 77lm/W L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results Wattage Equivalency: 50 LED Characteristics <hr/> Color Accuracy (CRI): 80 Color Temperature: 5000K	Electrical <hr/> Power Factor: >0.7 Dimmable: Yes, down to 10% Input Voltage: 120V Operating Frequency: 60 Hz Operating Temperature: -20°C to 45°C Construction <hr/> Bulb Shape: PAR16 Enclosure Material: Plastic Housing Finish: White	Base Type: GU10 Optical <hr/> Beam Angle: 35° Other <hr/> Technology EQ: Halogen Warranty (Years): 3 years Compliance <hr/> UL Listed: Yes Environment/Fixture Rating: Damp / Enclosed Rohs: Mercury and UV free. RoHS-compliant components. FCC: Complies with Part 15B of the FCC Rules

Technical Specifications (continued)

Model Number for Certification:

R10062(GU10-4.5-850-35D-DIM)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
10	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	10	0	0	0
PALLET	3120	0	0	0

Dimension

