HID-36-EX39-850-BYP/3SP

Project: Type:	Prepared By:	Date:
UPC: 192552005	Lamp inclu accessories Rated for u 4kV surge p 50,000-Hou 5-Year, No-	se in enclosed and open fixtures in dry or damp locations protection built in
Performance Product Type:	Model Number for Certification: H10067(HID-36-EX39-850-BYP/3SP)	Flicker: <30%
Technical Specifications Performance Product Type: HID Replacement Input Wattage: 36W Lumens (Nominal):	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements.	
Performance Product Type: HID Replacement Input Wattage: 36W	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to	<30% Operating Temperature: -30°C to 60°C Input Voltage:
Performance Product Type: HID Replacement Input Wattage: 36W Lumens (Nominal): 5,400lm Efficacy: 150lm/W	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PL43238D7M5S LED Characteristics Color Temperature:	<30% Operating Temperature: -30°C to 60°C Input Voltage: 100-277V Operating Frequency: 50/60Hz
Performance Product Type: HID Replacement Input Wattage: 36W Lumens (Nominal): 5,400lm Efficacy:	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PL43238D7M5S LED Characteristics Color Temperature: 5000K Color Accuracy (CRI): >80 CRI Electrical	<30% Operating Temperature: -30°C to 60°C Input Voltage: 100-277V Operating Frequency: 50/60Hz Construction Bulb Shape:
Performance Product Type: HID Replacement Input Wattage: 36W Lumens (Nominal): 5,400lm Efficacy: 150lm/W L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results Wattage Equivalency: 150W Metal Halide or High Pressure Sodium Compliance UL Listed:	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PL43238D7M55 LED Characteristics Color Temperature: 5000K Color Accuracy (CRI): >80 CRI Electrical THD: <20%	<30% Operating Temperature: -30°C to 60°C Input Voltage: 100-277V Operating Frequency: 50/60Hz Construction Bulb Shape: Post top (sensor) Base Type:
Performance Product Type: HID Replacement Input Wattage: 36W Lumens (Nominal): 5,400lm Efficacy: 150lm/W L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results Wattage Equivalency: 150W Metal Halide or High Pressure Sodium Compliance	H10067(HID-36-EX39-850-BYP/3SP) DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PL43238D7M55 LED Characteristics Color Temperature: 5000K Color Accuracy (CRI): >80 CRI Electrical THD:	<30% Operating Temperature: -30°C to 60°C Input Voltage: 100-277V Operating Frequency: 50/60Hz Construction Bulb Shape: Post top (sensor) Base Type: EX39 Endcap Material:

RAB

HID-36-EX39-850-BYP/3SP

Technical Specifications (continued)

Optical

Beam Angle: 360°

Installation

Installation Orientation:

Vertical and Horizontal

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at <u>rablighting.com/warranty.</u>


Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity	
8	1	

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	15.4	11.8	15
PALLET	432	48	40	41.04





Dimension