

Project:	Type:	Prepared By:	Date:
-----------------	--------------	---------------------	--------------



Features and Benefits

- Replaces traditional metal halide or high pressure sodium HID lamp
- Adjustable wattage and CCT allows for in-field customization
- Integral driver enables lamp to be wired directly to line voltage without need for an external driver or ballast
- Rated for use in enclosed fixtures in dry or damp locations
- 4kV surge protection built in
- 50,000-Hour lifespan
- Environmentally friendly, no mercury used
- UL Listed, DLC Listed (select models)
- 5-Year, No-Compromise Warranty

Technical Specifications		
Performance	Model Number for Certification:	Operating Temperature:
Product Type: HID Replacement	H10077(HIDFA-135S-V-EX39-8CCT-BYP)	-30°C to 50°C
Input Wattage: 8.8-135W	DLC Listed: This product is on the Design Lights Consortium (DLC) Qualified Products List and is eligible for rebates from DLC Member Utilities. Designed to meet DLC 5.1 requirements. DLC Product Code: PLV4B3FLLDON	Input Voltage: 120-277V
Lumens (Nominal): 1,300-20,000lm	LED Characteristics	Operating Frequency: 60 Hz
Efficacy: 147.7-148.1lm/W	Color Temperature: 3000K/4000K/5000K	Construction
L70 Lifespan: 50,000-Hour LED lifespan based on IES LM-70 results	Color Accuracy (CRI): 80 CRI	Bulb Shape: Round
Wattage Equivalency: 400W Metal Halide or High Pressure Sodium	Electrical	Base Type: EX39
Compliance	THD: <20%	Endcap Material: Aluminum
UL Listed: Suitable for damp locations	Power Factor: 0.9	Enclosure Material: Plastic
Enclosed Fixtures: Suitable for use in enclosed fixtures	Dimmable: Stepless dimming by rotate switch	Optical
		Beam Angle: 90°

Technical Specifications (continued)

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	2	17.5	14.4	18
PALLET	36	44.49	36.61	45.67

Dimension

