



UPC: 192552015684



Weight: 0.1 lbs

Project:	Type:
Prepared By:	Date:

Driver Info		LED Info	
Type	Constant Current	Watts	6W
120V	0.07A	Color Temp	2200K-4500K
208V	N/A	Color Accuracy	90 CRI
240V	N/A	L70 Lifespan	15,000 Hours
277V	N/A	Lumens	800 lm
Input Watts	6W	Efficacy	133

Technical Specifications

Performance

Product Type:

Bluetooth-Enabled Filaments

Input Wattage:

6W

Lumens (Nominal):

800lm

Efficacy:

133lm/W

Lifespan:

15,000-Hour LED lifespan based on IES LM-80 results and TM-21 calculations

LED Characteristics

Color Accuracy (CRI):

>90 CRI

Color Temperature:

2200K-4500K

Electrical

Power Factor:

0.7

Dimming:

Dimmable via Lightcloud Blue mobile app

Flicker:

<30%

Operating Temperature:

-20°C to 45°C (-4°F to 113°F)

Input Voltage:

120V

Operating Frequency:

60Hz

Construction

Material:

Glass

Bulb Shape:

G25

Base Type:

E26, Medium Screw Base

Optical

Beam Angle:

360°

Compliance

UL Listed:

Suitable for wet locations

Fixture Rating:

Enclosed

Other

Warranty:

RAB warrants that our LED products will be free from defects in materials and workmanship for a period of three (3) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.


Buy American Act Compliance:

RAB values USA manufacturing! Upon request, RAB may be able to manufacture this product to be compliant with the Buy American Act (BAA). Please contact customer service to request a quote for the product to be made BAA compliant.

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	6	10.35	6.97	6
PALLET	528	42.99	39.21	23.72

Dimension



Features

Direct Connect to the Lightcloud Blue mobile app via Bluetooth, no Gateway or Hub required

Use mobile device to configure features for On/Off Control, Dim Level, Color Temperature, Schedules, Scenes, SmartShift and more.

Tunable White 2200-4500K with smooth transition between color temperatures

Circadian SmartShift Capable to sync with local sunrise/sunset

Suitable for open or enclosed fixtures in dry, damp, or wet environments.

Title 20 Compliant, ENERGY STAR® compliant, UL Listed

Ordering Matrix

Family	Bulb	Wattage	Base Type	CRI/Color Temp	Type	Finish	SmartShift
LCB	G25	6	E26	9TW	F	C	SS
	A19 = A19 G25 = G25 ST19 = ST19 B11 = B11	5 = 5W 6 = 6W	E26 = E26 Base	9TW = 90 CRI, Tunable White	F = Filament	C = Clear	SS = SmartShift