

Project: _____ Type: _____ Prepared By: _____ Date: _____



Features and Benefits

- Energy efficient replacement for incandescent and halogen Small diameter reflectors
- Constructed from durable materials which lowers risk of breakage
- Rated for use in enclosed and open fixtures in dry or damp locations
- Single optic and full face lens for precise beam angle control
- Longer lifespan compared to legacy equivalents minimizes replacement and maintenance costs
- ENERGY STAR Compliant, UL Listed

Technical Specifications		
Performance <hr/> Product Type: Small-Reflector Input Wattage: 7.5W Lumens (Nominal): 570lm Efficacy: 76lm/W L70 Lifespan: 25,000-Hour LED lifespan based on IES LM-70 results Wattage Equivalency: 50 LED Characteristics <hr/> Color Accuracy (CRI): 80 Color Temperature: 2700K	Electrical <hr/> Power Factor: >0.9 Dimmable: Yes, down to 10% Input Voltage: 12V Operating Frequency: 60 Hz Operating Temperature: -20°C to 45°C Construction <hr/> Bulb Shape: MR16 Enclosure Material: Aluminum Housing Finish: White	Base Type: GU5.3 Optical <hr/> Beam Angle: 35° MBCP: 1315 Other <hr/> Technology EQ: Halogen Warranty (Years): 3 years Compliance <hr/> UL Listed: Yes Environment/Fixture Rating: Damp / Enclosed Energy Star ID: 2356094

Technical Specifications (continued)

Rohs:

Mercury and UV free. RoHS-compliant components.

FCC:

Complies with Part 15B of the FCC Rules

Model Number for Certification:

R10056(MR16-7.5-827-35D-DIM)

Minimum Compartment Size

Length x Width x Height [in]	Lamp Quantity
8	1

Case and Pallet Dimensions

	QTY	LENGTH (in)	WIDTH (in)	HEIGHT (in)
CASE	12	0	0	0
PALLET	4536	0	0	0

Dimension

