

# PL Ballast Hybrid - Omnidirectional



7W PLC

9W PLC

Compact 2Pin, PL Ballast Hybrid, Omnidirectional Light, UL Type A+B Lamps

PROJECT:

DATE:

TYPE:

PREPARED BY:



## KEY FEATURES

- Omnidirectional light distribution
- Suitable for horizontal or vertical installation
- Replaces 13W and 18W G24d & G24q CFL lamps
- Plug and Play on existing Magnetic CFL ballasts or can be wired directly to line voltage without need for an external driver or ballast
- Compatible with G24q / GX24q (4-pin CFL) installations
- 50,000-hour lifespan based on IES LM-80 and TM-21 calculations
- Environment friendly, no mercury used
- UL Listed, UL Classified
- Rated for use in enclosed and open fixtures in dry or damp locations
- Non-Dimmable
- 5- Year, No-Compromise Warranty



## PERFORMANCE

Catalog Number	Equivalency	Input Wattage	Lumen	Efficacy	Color Temperature	CRI	L70 Lifespan
PLC-7-O-835-HYB	13W/18W G24d & G24q	7W	880	126	3500K	80	50,000
PLC-7-O-840-HYB	13W/18W G24d & G24q	7W	900	129	4000K	80	50,000
PLC-9-O-827-HYB	26W/32W G24d & G24q	9W	1150	128	2700K	80	50,000
PLC-9-O-830-HYB	26W/32W G24d & G24q	9W	1200	133	3000K	80	50,000
PLC-9-O-835-HYB	26W/32W G24d & G24q	9W	1250	139	3500K	80	50,000
PLC-9-O-840-HYB	26W/32W G24d & G24q	9W	1250	139	4000K	80	50,000

## TECHNICAL SPECIFICATIONS

### CONSTRUCTION

<b>Product Type</b> Compact	<b>Lens Finish</b> Frosted
<b>Bulb Shape</b> PLC-O	<b>Base Type</b> 2-Pin G24d
<b>Enclosure Material</b> Polycarbonate	<b>Beam Angle</b> 360°
<b>Endcap Finish</b> White	

### COMPLIANCE

- Safety Listing**  
UL Listed, UL Classified
- Environment/Fixture Rating**  
Damp / Enclosed
- FCC**  
Complies with Part 15 of the FCC Rules.
- RoHS**  
Mercury and UV free. RoHS-compliant components.

### INSTALLATION METHOD

UL Type A with Magnetic ballast & UL Type B (Dual Mode)

### ELECTRICAL

- THD**  
≤20%
- Power Factor**  
>0.9
- Input Voltage**  
120-277V
- Operating Frequency**  
50/60Hz
- Operating Temperature**  
-20°C to 45°C
- Note**  
All values are typical (tolerance +/- 10%)


### OTHER

- Warranty**  
RAB warrants that our LED products will be free from defects in materials and workmanship for a period of five (5) years from the date of delivery to the end user, including coverage of light output, color stability, driver performance and fixture finish.  
  
RAB's warranty is subject to all terms and conditions found at [rablighting.com/warranty](http://rablighting.com/warranty).

## DIMENSIONS


### PLC: 7W (Hybrid)

Weight: 0.2 lbs



### PLC: 9W (Hybrid)

Weight: 0.2 lbs



# PL Ballast Hybrid - Omnidirectional



## ORDERING INFO

Catalog Number	Model Number (DLC/Energy Star)	UPC	Case Pack
PLC-7-O-835-HYB	T10188 (PLC-7-O-835-HYB)	019813915562	12
PLC-7-O-840-HYB	T10189 (PLC-7-O-840-HYB)	019813915579	12
PLC-9-O-827-HYB	T10194 (PLC-9-O-827-HYB)	019813916286	12
PLC-9-O-830-HYB	T10195 (PLC-9-O-830-HYB)	019813916293	12
PLC-9-O-835-HYB	T10196 (PLC-9-O-835-HYB)	019813916309	12
PLC-9-O-840-HYB	T10197 (PLC-9-O-840-HYB)	019813916439	12

## ORDERING MATRIX

Family	Wattage	Mounting Orientation	CRI/Color Temp	Installation Type
<b>PLC</b>	-	-	<b>O</b>	-
<b>PLC</b> Plug-in Cluster	<b>7</b> 7W <b>9</b> 9W	<b>O</b> Omnidirectional	<b>840</b> 80 CRI, 4000K <b>835</b> 80 CRI, 3500K <b>830*</b> 80 CRI, 3000K <b>827*</b> 80 CRI 2700K <i>* Only for 9W</i>	<b>HYB</b> Dual Mode UL Type A or UL Type B