

GL-12 SERIES OUTDOOR LIGHTING


GL-12V-24W-30K-BR
GL-12V-24W-40K-BR
GL-12V-24W-50K-BR



Selection:



Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



6 3/4"(H) x 5"(W) x 5 1/2"(D)

The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Features

- Die-cast Aluminum Housing with Powder Coat Finish (Dark Bronze)
- 1/2" Threaded Knuckle Stem
- 7-Year Warranty
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors

Technical Specifications

Electrical:

- Voltage: 12V
- Power Factor: >0.92
- Wattage: 24W
- Efficacy: 90 LPW

Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish (Dark Bronze)
- Solid State Lighting Technology for Long Life, No Maintenance Needed and High-Efficiency
- High Conductive Aluminum LED Board
- 8-1/2" PC Spike Included
- 1/2" Threaded Knuckle Stem
- IP Rating: IP65
- Operating Temperature: -40°F to 104°F
- Suitable for Wet Locations
- Rotatable Shroud with Set Screw
- 7-Year Warranty

Lighting:

- Lens Type: Plaid Tempered Glass + Aluminum Reflectors
- Total Lumens: 2160LM
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 90°

Applications:



- The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Other Models:


- 12W | 1080LM | GL-12V-12W-30K-BR
- 12W | 1080LM | GL-12V-12W-40K-BR
- 12W | 1080LM | GL-12V-12W-50K-BR



Photometrics: GL-12V-24W



BUG Rating: B2-U2-G0



Area 30'x 30' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: GL-12V-24W

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
GL-12V-24W-30K-BR	24W	12V	2160LM	3000K	B2-U2-G0	90
GL-12V-24W-40K-BR			2160LM	4000K		
GL-12V-24W-50K-BR			2160LM	5000K		

Sample Ordering

Model	Volt	Watt	Color Temp.	Color
GL	12V	24W		BR
			30K = 3000K 40K = 4000K 50K = 5000K	

Accessories:

Blank = No Option For Accessories

A-41-BR = 1/2" NPT Hub, Cast Aluminum, Bronze Powder Coat Finish

LSWN1 = Bag of 24, Waterproof Wire Connectors, For Up to Two 14-2 + One 16-2 Cables

LSWN2 = Box of 24, Waterproof Wire Connectors, For Up to Three 12-2 Cables

LSWN2-100 = Jar of 100, Waterproof Wire Connectors, For Up To Three 12-2 Cables

A-41-S = Tree Mounting Base

LG-SMB-BZ = 12V Brass Landscape Tree or Surface Bracket, Antique Bronze Finish

BC-13 = 13" Bungee Cords with Hooks

BC-18 = 18" Bungee Cords with Hooks

BC-24 = 24" Bungee Cords with Hooks

BC-32 = 32" Bungee Cords with Hooks

ACCESSORIES:



A-41-BR

1/2" NPT hub, Cast aluminum, Bronze Powder coat finish



LSWN1

Bag of 24, Waterproof wire connectors, for up to two 14-2 + one 16-2 cables



LSWN2

Box of 24, Waterproof wire connectors, for up to three 12-2 cables



LSWN2-100

Jar of 100, Waterproof wire connectors, for up to three 12-2 cables



A-41-S

Tree mounting base



LG-SMB-BZ

12V brass landscape tree or surface bracket, antique bronze finish



BC-13/18/24/32

13"/18"/24"/32" Bungee cords with hooks

Example:

1. GL-12V-24W-30K-BR

(For GL 12V 24W 30K Fixture 120-277V)

2. GL-12V-24W-30K-BR

(For GL 12V 24W 30K Fixture 120-277V)

A-41-BR

(1/2" NPT Hub, Cast Aluminum, Bronze Powder Coat Finish)

WESTGATE

Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com | www.westgatecontrols.co

