


RSL SERIES

RSL6-MCT5-WP
WET LOCATION LED ULTRA SLIM RECESSED LIGHTS
MCT5 Multi Color Temperature (Selectable)



Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



6 6/7" x 6 2/3"

LED DOWNLIGHTS (SMOOTH TRIM) - 6" ROUND Ideal for New As Well As Old Residential And Commercial Constructions.

Features

- 6" Smooth Recessed Trim
- Multi CCT (Selectable Switch On the Back Of The Driver)
- Isolated Driver For Improved Thermal Management
- 5-Year Warranty
- Spun Aluminum With White Powder Coat Finish

Technical Specifications

Electrical:

- Voltage: 120V AC
- Output Voltage: 36VDC
- Power Factor: >0.90
- Wattage: 15W
- Efficacy: 75 LPW
- Total Harmonic Distortion: $\leq 15\%$

Mechanical:

- 1/4" Thick
- Up to 9 AWG18 Wires
- Die-Cast Aluminum With White Powder Coat Finish
- Pot Light Housing Is Not Required Even For Insulated Ceiling
- Junction box 1" Thick Included With Fixture
- Typel Crated: Approved For Direct Contact With Insulation
- Maximum Ambient Temperature: -40°F to 104°F
- Suitable For Wet Location

Lighting:

- Multi CCT (Selectable Switch On The Back Of The Driver)
- Dimming: Dimmable Down to 10% Using A Standard TRIAC LED Dimmer
- Lens: 0.125" White Translucent Acrylic
- Can Rotate After Installation to Align
- LED: Seoul DOB (Driver On Board) Technology
- Optics: White Translucent Acrylic
- Total Lumens: 1125LM
- Color Temperatures: 2700K/ 3000K/ 3500K/ 4000K/ 5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 100°-110°

Applications:


- LED recessed trims have been designed to be a flexible lighting solution for new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:


• 6W | 400LM | RSL3-MCT5-WP • 9W | 630LM | RSL4-MCT5-WP • 18W | 1350LM | RSL8-MCT5-WP • 20W | 1500LM | RSL10-MCT5-WP • 24W | 1800LM | RSL12-MCT5-WP



Photometrics: RSL6-MCT5-WP



BUG Rating: B1-U2-G1



15W 5000K, Area 35'x 35' Mounting Height: 9'

Other Views:



Side View



Front View



Junction box 1-1/4" thick included with fixtures

Back View

Performance Table: RSL6-MCT5-WP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
RSL6-MCT5-WP	15W	120V	1125LM	2700K	B1-U2-G1	75
				3000K		
				3500K		
				4000K		
				5000K		

Sample Ordering

Model Color Temp.

RSL6 - MCT5 - WP

Accessories:

Blank = No Option For Accessories
RSL-EXT-10FT-MCT = 10 FT. EXTENSION CABLE FOR USE WITH ALL SLIM LIGHT
RSL6-RI-13 = 6" ROUND ROUGH-IN PLATE, 13" LONG
RSL6-RI = 6" ROUND ROUGH-IN PLATE, 26" LONG
RSL-346-RIBH = 3", 4", 6" (ADJUSTABLE) ROUND GALVANIZED PLATE WITH BAR HANGERS
RSL6-GR = GOOF RING FOR 6IN LIGHTS WITH BUTTERFLY WINGS
RSL6-TRM-BK = 6" Black Clip-on Trim
RSL6-TRM-ORB = 6" Oil-rubbed Bronze Clip-on Trim
RSL6-TRM-CU = 6" Copper Clip-on Trim
RSL6-TRM-BZ = 6" Bronze Clip-on Trim
RSL6TRM-BN = 6" Brushed Nickel Clip-on Trim
RSL6-TRM-CH = 6" Chrome Clip-on Trim

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-RSL = EXTERNAL BATTERY BACKUP

ACCESSORIES:



RSL6-RI-13
6" Round Rough-in Plate,
13" Long



RSL-EXT-10FT-MCT
10 Ft. Extension Cable For use
with all Slim Light



RSL-346-RIBH
3", 4", 6" (Adjustable) Round Galvanized
plate with Bar Hangers




RSL6-RI
6" Round Rough-in Plate,
26" Long



Clip-on Trims
BK ORB CU BZ BN CH



RSL6-GR
Goof Ring For 6in Lights With Butterfly
Wings



FACTORY-INSTALLED OPTION:



OPT-EM-RSL
EXTERNAL BATTERY BACKUP



Compatible Dimmer List:

MODEL NO.	BRAND
6631-1LT	LEVITON
MACL-153MLH-AL	LUTRON
TGCL-153PH-LA	LUTRON
DVW-603PGH-WH	LUTRON
CT-600PR-WH	LUTRON
LGCL-153PHL-IV	LUTRON
TGCL-153PH-LA	LUTRON
LSLV603PWV	LUTRON
6674-POW	LEVITON
DVCL-153P	LUTRON
MSCL-OP153P	LUTRON
CTCL-153P	LUTRON
MACL-153M	LUTRON
HCL453PTCCCV6	PASS & SEYMOUR
LSLV603PWV	PASS & SEYMOUR

