


TC SERIES OUTDOOR LIGHTING

TC-FL-36W-RGBW-BT-BR
BLUETOOTH WG APP COMPATIBLE RGBW FLOOD LIGHT



The fixture has classic traditional appearance, professional light distribution design, 60-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



9 1/5"(H) x 7 2/5"(W) x 5 1/5"(D)

Features

- Die-cast Aluminum Housing with Powder Coat Finish
- Adjustable Yoke Bracket
- 7-Year Warranty
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors

Technical Specifications

Electrical:

- Voltage: 120-277V
- Power Factor: >0.9
- Wattage: 36W
- Efficacy: 36 LPW
- Operating Voltage: Max 900 mA, Max 36VDC
- Bluetooth Connection Range: Approximately 30 feet (10 meters). Maximum Communication Range Will Vary Depending On Obstacles (Person, Metal, Wall, etc.) Or Electromagnetic Environment.

Mechanical:

- This Fixture is Bluetooth mesh Enabled. Bluetooth mesh networking enables many-to-many (m:m) device communications and is optimized for creating large-scale device networks. It is ideally suited for control monitoring and automation solutions that require tens, hundreds or thousands of devices to communicate with one another
- Die-cast Aluminum Housing with Powder Coat Finish Solid State Lighting Technology for Long Life, No Maintenance Needed and High-Efficiency
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors
- High Conductive Aluminum LED Board
- Adjustable Yoke Bracket
- Operating Temperature: -40°F to 104°F
- IP Rating: IP65, Suitable for Wet Locations
- 7-Year Warranty

Lighting:



- Dimming: Dimmable Through Phone App
- Total Lumens: 930LM (Warm White)
1300LM (Cool White)
- Color Temperatures: RGBW Selectable Through Phone App
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 60°

Applications:


- The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations



Photometrics: TC-FL-36W-RGBW-BT-BR



BUG Rating: B1-U2-G0



36W White, Area 20'x 20' Mounting Height: 9'

Other Views:



Side View



Front View




Back View

Performance Table: TC-FL-36W-RGBW-BT-BR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
TC-FL-36W-RGBW-BT-BR	36W	120-277V	930LM(Single White) 1300LM(Maximum Power)	RGBW	B1-U2-G0	36

Sample Ordering

Model	Flood Light	Watt	Color Temp.	Bluetooth	Color
TC	FL	36W	RGBW	BT	BR



- For Setting Up The Light(s), Initial Internet Connection or Mobile Data Is Required.
- After the Initial Setup, Internet Connection is not Necessary Anymore. The lights Can Be Controlled with The Mobile App on The Phone or Tablet. Features Such as Dimming, Changing Colors, Lights Scenes, etc.
- Scheduling Feature Requires Internet Connection.
- Bluetooth Devices Need a Gateway (Sold Separately) In Order to Connect to WiFi Network (Internet)

