



JOB NAME: _____

DATE: _____

TYPE: _____



ULR-IP54-16F-HO-27K
 ULR-IP54-16F-HO-30K
 ULR-IP54-16F-HO-40K
 ULR-IP54-16F-HO-50K

24V DAMP LOCATION HIGH OUTPUT LED RIBBON

Ideal for undercabinet, soffit, display cases and toe kick lighting.

ELECTRICAL SPECIFICATIONS:

- Voltage: 24VDC (LED driver required)
- Wattage: 4.4W per ft.
- Max Run: 20ft.
- Efficacy: 75~79LM/W per ft.

HOUSING SPECIFICATIONS:

- Cutting increment: Every 4 inches
- 3M double sided tape(9474LE) is preinstalled
- Operating temperature: -4°F - 104°F
- IP rating: IP54

CERTIFICATIONS: UL



DIMENSIONS:

16.4'(L) x 0.4"(W)

| MODEL | WATTS PER FT. | VOLTAGE | LUMENS PER FT. | COLOR TEMP | REEL LENGTH | MAX RUN |
|---------------------|---------------|---------|----------------|------------|-------------|---------|
| ULR-IP54-16F-HO-27K | 4.4W | 24VDC | 310LM | 2700K | 16.4FT. | 20FT. |
| ULR-IP54-16F-HO-30K | 4.4W | 24VDC | 310LM | 3000K | 16.4FT. | 20FT. |
| ULR-IP54-16F-HO-40K | 4.4W | 24VDC | 330LM | 4000K | 16.4FT. | 20FT. |
| ULR-IP54-16F-HO-50K | 4.4W | 24VDC | 350LM | 5000K | 16.4FT. | 20FT. |

OPTIONAL ACCESSORIES:



ULR-IN-HO-COUP-6I-WR
 ULR-IN-HO-COUP-3F-WR



ULR-IN-HO-COUP-NO-WR



ULR-IN-HO-CONN-6I-WR
 ULR-IN-HO-CONN-3F-WR
 ULR-IN-HO-CONN-6I-PT
 ULR-IN-HO-CONN-3F-PT

| MODEL | DESCRIPTION |
|------------------------|--|
| ULR-IP54-HO-COUP-6I-WR | Coupling to connect 2 high output ribbons, 6" |
| ULR-IP54-HO-COUP-3F-WR | Coupling to connect 2 high output ribbons, 3' |
| ULR-IP54-HO-COUP-NO-WR | Coupling to connect 2 high output ribbons, no wire |
| ULR-IP54-HO-CONN-6I-WR | Power feed cable, 1side ribbon connector, 1 side female socket to driver |
| ULR-IP54-HO-CONN-3F-WR | Power feed cable, 1side ribbon connector, 1 side female socket to driver |
| ULR-IP54-HO-CONN-6I-PT | Power feed cable, 1side ribbon connector, 1 side open end |
| ULR-IP54-HO-CONN-3F-PT | Power feed cable, 1side ribbon connector, 1 side open end |

LIGHTING SPECIFICATIONS:

- Dimming: Dimmable using a magnetic driver
- LED: SMD2835 chip spaced 5/8" on center, 19 per foot, 0.23 wats each chip
- LED Type: SMD2835
- Total lumens: 310~350LM per ft.
- Color temperature: 2700K/3000K/4000K/5000K
- Color rendering index: 90
- Beam Angle: 120°

WARRANTY: 5 years

